

Statement of Basis of the Federal Operating Permit

Equistar Chemicals, LP

Site Name: Equistar Chemicals Channelview Complex
Area Name: Equistar Channelview Facility
Physical Location: 8280 Sheldon Road
Nearest City: Channelview
County: Harris

Permit Number: O1426
Project Type: Minor Revision

The North American Industry Classification System (NAICS) Code: 325110
NAICS Name: Petrochemical Manufacturing

This Statement of Basis sets forth the legal and factual basis for the draft changes to the permit conditions resulting from the minor revision project in accordance with 30 TAC §122.201(a)(4). The applicant has submitted an application for a minor permit revision per §§ 122.215-217. This document may include the following information:

- A description of the facility/area process description;
- A description of the revision project;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: February 28, 2018

Operating Permit Basis of Determination

Description of Revisions

This minor revision application:

1. Updates the site wide terms and conditions regarding 40 CFR Part 61, Subpart FF.
2. Adds PBR 106.261/262 to the site wide authorizations.
3. Updates version issue date of NSR permits 24887, 24677, 1768 and 2933 to the site wide authorizations.
4. Removes Municipal Solid Waste permit 1768 from FOP.
5. Updates MACT FFFF applicable requirements for several units/groups.
6. Applies new Standard Permits 144030 and 143753 site wide and to emission sources EUTFL1701 and EUTFL1701V. Updates the renewal of Standard Permits 84019 and 84079.
7. Adds new storage tanks. Removes unused tanks. Reassigns various storage tanks to new groupings based on applicable requirements.
8. Replaces engines ZMSENAIS, and removes OP2EN1.

Permit Area Process Description

ECCC consists of thirteen different process areas with many functions, emissions sources, and responsibilities. The Olefins I area (OP1) and Olefins II area (OP2) consist of a cracking and quench area, a compression and fractionation area, a pyrolysis gasoline hydrogenation area, a utilities area and a tank storage area. The C5 Recovery Unit, or Isoprene Unit, separates and purifies the components in a crude C5 feed-stream. The finished products, such as isoprene, piperylene, and dicyclopentadiene (DCPD) are sold. The C4 Recovery Unit feeds crude C4 from the Olefins unit and produces butadiene and Raff I and recycles butanes and butenes. The Alkylation Process Unit reacts light olefins with isobutane in the presence of sulfuric acid to form the alkylate product, which is used in gasoline formulations. The Polybutadiene Resin Unit (Poly BD) manufactures homopolymer resins of butadiene. The Polybutadiene liquid resin product is sent to storage for blending, packaging, and/or shipment. The Styrene Maleic Anhydride (SMA) unit manufactures SMA copolymer resin from styrene and maleic anhydride monomer feeds. The Barge Dock, located on the Houston Ship Channel, consists of two piers that can load from either side, for a total of four loading berths. The dock is used to load and unload materials for the Equistar site and for the adjacent Lyondell Chemical site as well. The materials authorized for transfer by Equistar at the dock include methanol, pyrolysis fuel oil, pyrolysis gas oil, olefin feed stocks, pyrolysis gasoline, and benzene. The materials authorized for transfer by Lyondell at the dock include styrene monomer, ethylbenzene, MTBE, ETBE, acetophenone, polyols, and tertiary butyl alcohol. The Isopropanol Operating Area (IPOH) produces isopropanol by purification of crude acetone, gas compression, hydrogenation of acetone, and isopropanol recovery. The East Utilities area is comprised of miscellaneous sources including flares, oil/water separators, a hydroblasting area, and several wastewater treatment systems. The Benzene/Toluene (B/T) Unit produces benzene and toluene from a feedstock of hydrogenated pyrolysis gasoline (naphtha) produced in the Olefins Units. The Methanol Unit produces high purity methanol from light hydrocarbon feedstock. The Methyl Tertiary Butyl Ether (MTBE) Unit is a chemical manufacturing process unit.

FOPs at Site

The "application area" consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O3585

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, PM, NOX, HAPS, CO
------------------	------------------------

Reading State of Texas's Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
 - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
 - Additional Monitoring Requirements
 - New Source Review Authorization Requirements
 - Compliance Requirements
 - Protection of Stratosphere Ozone
 - Permit Location
 - Permit Shield (30 TAC § 122.148)
- Attachments
 - Applicable Requirements Summary
 - Unit Summary
 - Applicable Requirements Summary
 - Additional Monitoring Requirements
 - Permit Shield
 - New Source Review Authorization References
 - Compliance Plan
 - Alternative Requirements
- Appendix A
 - Acronym list
- Appendix B
 - Copies of major NSR authorizations

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the "index number," detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Appendix B

Copies of major NSR authorizations applicable to the units covered by this permit have been included in this Appendix, to ensure that all interested persons can access those authorizations.

Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3 for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

Stationary Vents subject to 30 TAC Chapter 111 not addressed in the Special Terms and Conditions

All other stationary vents subject to 30 TAC Chapter 111 not covered in the Special Terms and Conditions are listed in the permit's Applicable Requirement Summary. The basis for the applicability determinations for these vents are listed in the Determination of Applicable Requirements table.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	Yes
Nonattainment New Source Review (NNSR)	Yes
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes

Regulatory Program	Applicability (Yes/No)
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CSAPR (Cross-State Air Pollution Rule)	No

Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

- Office activities such as photocopying, blueprint copying, and photographic processes.
- Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
- Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
- Outdoor barbecue pits, campfires, and fireplaces.
- Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
- Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
- Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
- Storage and handling of sealed portable containers, cylinders, or sealed drums.
- Vehicle exhaust from maintenance or repair shops.
- Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
- Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
- Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.

13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feed water) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an

applicable requirement, it will be explained in detail in the portion of this document entitled “Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected.”

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled “Basis for Applying Permit Shields” specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPCARFLR	40 CFR Part 65, Subpar D (CAR)	65CAR-FL	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
GRPCARFURN	40 CFR Part 65, Subpar D (CAR)	65CAR-FUR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
MEOHFLARE	40 CFR Part 65, Subpar D (CAR)	65CAR-FL	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
MEOHT7001	40 CFR Part 65, Subpar D (CAR)	65RRRCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
MEORXR7001	40 CFR Part 65, Subpar D (CAR)	65RRRCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
MEOTW7001	40 CFR Part 65, Subpar D (CAR)	65NNNCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
MEOTW7002	40 CFR Part 65, Subpar D (CAR)	65NNNCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
OFXTW4371	40 CFR Part 65, Subpar D (CAR)	65NNNCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP1TW3453	40 CFR Part 65, Subpar D (CAR)	65NNNCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
OP1TW3616	40 CFR Part 65, Subpar D (CAR)	65NNNCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
OP1TW3617	40 CFR Part 65, Subpar D (CAR)	65NNNCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
OP2TW4616	40 CFR Part 65, Subpar D (CAR)	65NNNCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
OP2TW4617	40 CFR Part 65, Subpar D (CAR)	65NNNCAR	UNIT TYPE = EMISSION UNIT NSPS NNN/RRR alternate compliance option	The rule citations were determined from an analysis of the rule text and the basis of determination.
EBGEG6901	30 TAC Chapter 117, Subchapter B	R7300-10	Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)] Fuel Fired = Petroleum-based diesel fuel	
EBGEG6901	40 CFR Part 60, Subpart IIII	60IIII-E	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before 07/11/2005.	
EBGEG6901	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2. Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP. Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002. Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii). Stationary RICE Type = Compression ignition engine	
EUTEN1	30 TAC Chapter 117, Subchapter	R71C1-1	Fuel Flow Monitoring = Unit is a diesel engine operating with a run time meter and using monthly fuel use records	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	B		<p>maintained for each engine per 30 TAC §§ 117.140(a)(2)(C), 117.340(a)(2)(C) or 117.440(a)(2)(C).</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(9)</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 3 g/hp-hr option</p> <p>CO Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>CO Monitoring System = Emissions monitored by means other than a CEMS or PEMS.</p> <p>EGF System Cap Unit = Engine is not used as an electric generating facility to generate electricity for sale to the electric grid.</p> <p>Type of Service = SRIC engine not meeting an exemption</p> <p>Fuel Fired = Petroleum-based diesel fuel</p> <p>NOx Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>Engine Type = Lean-burn</p> <p>NOx Reduction = None</p> <p>ESAD Date Placed in Service = Installed, modified, reconstructed or relocated on or after October 1, 2007.</p> <p>NOx Monitoring System = Maximum emission rate testing in accordance with 30 TAC § 117.8000</p> <p>Diesel HP Rating = Horsepower rating is 300 hp or greater, but less than 600 hp.</p>	
EUTEN1	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after 07/11/2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than 368 KW and less than 560 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder and engine is a constant-speed engine.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE was newly constructed after 07/11/2005.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture was after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2012.</p>	
EUTEN1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Performance Test = No previous performance test used, a performance test is conducted to demonstrate initial compliance</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Control Technique = Oxidation catalyst</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Emission Limitation = Limiting formaldehyde concentration from the stationary RICE exhaust</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	
EUTENEOC	30 TAC Chapter 117, Subchapter B	R7471-6	<p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
EUTENEOC	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP less than 100 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after December 19, 2002, but before June 12, 2006.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	
EUTENLAB	30 TAC Chapter 117, Subchapter B	R7471-5	<p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
EUTENLAB	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP less than 100 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	
EUTENPMDI	30 TAC Chapter 117, Subchapter B	R7471-4	<p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
EUTENPMDI	40 CFR Part 60, Subpart IIII	60IIII-E	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before 07/11/2005.</p>	
EUTENPMDI	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP less than 100 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii). Stationary RICE Type = Compression ignition engine	
EUTG1110	30 TAC Chapter 117, Subchapter B	R7471-10	Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)] Fuel Fired = Petroleum-based diesel fuel	
EUTG1110	40 CFR Part 60, Subpart IIII	60IIII-1	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after 07/11/2005. Diesel = Diesel fuel is used. Kilowatts = Power rating greater than or equal to 130 KW and less than or equal to 368 KW. Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement. Displacement = Displacement is less than 10 liters per cylinder and engine is a constant-speed engine. Service = CI ICE is an emergency engine. Standards = The emergency CI ICE meets the standards applicable to non-emergency engines. Commencing = CI ICE was newly constructed after 07/11/2005. Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions. Manufacture Date = Date of manufacture was after 04/01/2006. Model Year = CI ICE was manufactured in model year 2010.	
EUTG1110	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2. Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP. Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006. Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).	
EUTG1111	30 TAC Chapter 117, Subchapter B	R7471-11	Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)] Fuel Fired = Petroleum-based diesel fuel	
EUTG1111	40 CFR Part 60, Subpart IIII	60IIII-E	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before 07/11/2005.	
EUTG1111	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2. Brake HP = Stationary RICE with a brake HP greater than or equal to 100 HP and less than 250 HP.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
EUTP3301B	30 TAC Chapter 117, Subchapter B	R7471-12	<p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
EUTP3301B	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after 07/11/2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Displacement = Displacement is less than 10 liters per cylinder.</p> <p>Service = CI ICE is a fire-pump engine, an emergency engine certified to National Fire Protection Association requirements.</p> <p>Standards = The emergency CI ICE meets the standards applicable to non-emergency engines.</p> <p>Commencing = CI ICE was newly constructed after 07/11/2005.</p> <p>Compliance Option = Certified engine according to §60.4211(b)(1).</p> <p>Manufacture Date = Date of manufacture was after 07/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2007.</p>	
EUTP3301B	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	
EUTP803A	30 TAC Chapter 117, Subchapter B	R7471-13	<p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
EUTP803A	40 CFR Part 60, Subpart IIII	60IIII-E	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before 07/11/2005.	
EUTP803A	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
EUTP803B	30 TAC Chapter 117, Subchapter B	R7471-14	<p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
EUTP803B	40 CFR Part 60, Subpart IIII	60IIII-E	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before 07/11/2005.</p>	
EUTP803B	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
MEOPM3314	30 TAC Chapter 117, Subchapter B	R7471	<p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
MEOPM3314	40 CFR Part 60, Subpart IIII	60IIII-E	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before 07/11/2005.</p>	
MEOPM3314	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
OP1EN1	30 TAC Chapter 117, Subchapter B	R7300-1	<p>Fuel Flow Monitoring = Unit is a diesel engine operating with a run time meter and using monthly fuel use records maintained for each engine per 30 TAC §§ 117.140(a)(2)(C), 117.340(a)(2)(C) or 117.440(a)(2)(C).</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(9)</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 3 g/hp-hr option</p> <p>CO Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>CO Monitoring System = Emissions monitored by means other than a CEMS or PEMS.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>EGF System Cap Unit = Engine is not used as an electric generating facility to generate electricity for sale to the electric grid.</p> <p>Type of Service = SRIC engine not meeting an exemption</p> <p>Fuel Fired = Petroleum-based diesel fuel</p> <p>NOx Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>Engine Type = Lean-burn</p> <p>NOx Reduction = None</p> <p>ESAD Date Placed in Service = Installed, modified, reconstructed or relocated on or after October 1, 2007.</p> <p>NOx Monitoring System = Maximum emission rate testing in accordance with 30 TAC § 117.8000</p> <p>Diesel HP Rating = Horsepower rating is 300 hp or greater, but less than 600 hp.</p>	
OP1EN1	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after 07/11/2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than 368 KW and less than 560 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder and engine is a constant-speed engine.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE was newly constructed after 07/11/2005.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture was after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2012.</p>	
OP1EN1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Performance Test = No previous performance test used, a performance test is conducted to demonstrate initial compliance</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Control Technique = Oxidation catalyst</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Limiting formaldehyde concentration from the stationary RICE exhaust</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP1EN2	30 TAC Chapter 117, Subchapter B	R7300-2	Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)] Fuel Fired = Petroleum-based diesel fuel	
OP1EN2	40 CFR Part 60, Subpart IIII	60IIII-1	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after 07/11/2005. Diesel = Diesel fuel is used. Kilowatts = Power rating is greater than or equal to 130 KW and less than or equal to 368 KW. Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement. Displacement = Displacement is less than 10 liters per cylinder. Service = CI ICE is a fire-pump engine, an emergency engine certified to National Fire Protection Association requirements. Standards = The emergency CI ICE meets the standards applicable to non-emergency engines. Commencing = CI ICE was newly constructed after 07/11/2005. Compliance Option = Certified engine according to §60.4211(b)(1). Manufacture Date = Date of manufacture was after 07/01/2006. Model Year = CI ICE was manufactured in model year 2007.	
OP1EN2	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2. Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP. Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006. Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).	
OP1EN3	30 TAC Chapter 117, Subchapter B	R7300-3	Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)] Fuel Fired = Petroleum-based diesel fuel	
OP1EN3	40 CFR Part 60, Subpart IIII	60IIII-1	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after 07/11/2005. Diesel = Diesel fuel is used. Kilowatts = Power rating is greater than or equal to 130 KW and less than or equal to 368 KW. Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement. Displacement = Displacement is less than 10 liters per cylinder. Service = CI ICE is a fire-pump engine, an emergency engine certified to National Fire Protection Association requirements. Standards = The emergency CI ICE meets the standards applicable to non-emergency engines. Commencing = CI ICE was newly constructed after 07/11/2005.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture was after 07/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2010.</p> <p>Options = The CI ICE rated speed is less than 2650 RPMs.</p>	
OP1EN3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	
OP2EN1	30 TAC Chapter 117, Subchapter B	R7300-1	<p>Fuel Flow Monitoring = Unit is a diesel engine operating with a run time meter and using monthly fuel use records maintained for each engine per 30 TAC §§ 117.140(a)(2)(C), 117.340(a)(2)(C) or 117.440(a)(2)(C).</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(9)</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 3 g/hp-hr option</p> <p>CO Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>CO Monitoring System = Emissions monitored by means other than a CEMS or PEMS.</p> <p>EGF System Cap Unit = Engine is not used as an electric generating facility to generate electricity for sale to the electric grid.</p> <p>Type of Service = SRIC engine not meeting an exemption</p> <p>Fuel Fired = Petroleum-based diesel fuel</p> <p>NOx Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>Engine Type = Lean-burn</p> <p>NOx Reduction = None</p> <p>ESAD Date Placed in Service = Installed, modified, reconstructed or relocated on or after October 1, 2007.</p> <p>NOx Monitoring System = Maximum emission rate testing in accordance with 30 TAC § 117.8000</p> <p>Diesel HP Rating = Horsepower rating is 300 hp or greater, but less than 600 hp.</p>	
OP2EN1	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after 07/11/2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than 368 KW and less than 560 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder and engine is a constant-speed engine.</p> <p>Service = CI ICE is a non-emergency engine.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Commencing = CI ICE was newly constructed after 07/11/2005.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture was after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2013.</p>	
OP2EN1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Performance Test = No previous performance test used, a performance test is conducted to demonstrate initial compliance</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Control Technique = Oxidation catalyst</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Limiting formaldehyde concentration from the stationary RICE exhaust</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	
OP2EN2	30 TAC Chapter 117, Subchapter B	R7300-2	<p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
OP2EN2	40 CFR Part 60, Subpart IIII	60IIII-E	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before 07/11/2005.</p>	
OP2EN2	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after December 19, 2002, but before June 12, 2006.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
OP2EN3	30 TAC Chapter 117, Subchapter B	R7300-3	<p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>	
OP2EN3	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after 07/11/2005.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Displacement = Displacement is less than 10 liters per cylinder.</p> <p>Service = CI ICE is a fire-pump engine, an emergency engine certified to National Fire Protection Association requirements.</p> <p>Standards = The emergency CI ICE meets the standards applicable to non-emergency engines.</p> <p>Commencing = CI ICE was newly constructed after 07/11/2005.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture was after 07/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2009.</p> <p>Options = The CI ICE rated speed is less than 2650 RPMs.</p>	
OP2EN3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Service Type = Emergency use where the RICE does not operate as specified in 40 CFR §63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	
ZMSENAIS	30 TAC Chapter 117, Subchapter B	R71C1-1	<p>Fuel Flow Monitoring = Unit is a diesel engine operating with a run time meter and using monthly fuel use records maintained for each engine per 30 TAC §§ 117.140(a)(2)(C), 117.340(a)(2)(C) or 117.440(a)(2)(C).</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(9)</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 3 g/hp-hr option</p> <p>CO Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>CO Monitoring System = Emissions monitored by means other than a CEMS or PEMS.</p> <p>EGF System Cap Unit = Engine is not used as an electric generating facility to generate electricity for sale to the electric grid.</p> <p>Type of Service = SRIC engine not meeting an exemption</p> <p>Fuel Fired = Petroleum-based diesel fuel</p> <p>NOx Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>Engine Type = Lean-burn</p> <p>NOx Reduction = None</p> <p>ESAD Date Placed in Service = Installed, modified, reconstructed or relocated on or after October 1, 2007.</p> <p>NOx Monitoring System = Maximum emission rate testing in accordance with 30 TAC § 117.8000</p> <p>Diesel HP Rating = Horsepower rating is 300 hp or greater, but less than 600 hp.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ZMSENAIS	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after 07/11/2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder and engine is a constant-speed engine.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE was newly constructed after 07/11/2005.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture was after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2012.</p>	
ZMSENAIS	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	
EALTK17	30 TAC Chapter 115, Storage of VOCs	R5112-4A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK17	30 TAC Chapter 115, Storage of VOCs	R5112-4B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK17	30 TAC Chapter 115, Storage of	R5112-4C	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		<p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK17	30 TAC Chapter 115, Storage of VOCs	R5112-4D	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK32	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
EALTK32	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i.</p> <p>WW Tank Control = An external floating roof is operated and maintained per 40 CFR § 63.1062(a)(2).</p> <p>Notification = The referencing subpart requires notification of initial startup.</p> <p>Unslotted Guide Pole = The tank does not use an unslotted guide pole.</p> <p>Wiper or Seal = The wiper or seal of the unslotted guide pole is at or above the pole wiper.</p> <p>Seal Configuration = Mechanical shoe primary seal and a secondary seal.</p>	
EALTK33	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
EALTK33	40 CFR Part 60, Subpart Kb	60Kb-1	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
EALTK33	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i.</p> <p>WW Tank Control = An external floating roof is operated and maintained per 40 CFR § 63.1062(a)(2).</p> <p>Notification = The referencing subpart requires notification of initial startup.</p> <p>Unslotted Guide Pole = The tank does not use an unslotted guide pole.</p> <p>Wiper or Seal = The wiper or seal of the unslotted guide pole is at or above the pole wiper.</p> <p>Seal Configuration = Mechanical shoe primary seal and a secondary seal.</p>	
EALTK37	30 TAC Chapter 115, Storage of VOCs	R5112-8	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
EALTK37	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i.</p> <p>WW Tank Control = An internal floating roof is operated and maintained per 40 CFR § 63.1062(a)(1).</p> <p>Notification = The referencing subpart requires notification of initial startup.</p> <p>Unslotted Guide Pole = The tank does not use an unslotted guide pole.</p> <p>Wiper or Seal = The wiper or seal of the unslotted guide pole is at or above the pole wiper.</p> <p>Seal Configuration = Mechanical shoe seal.</p>	
EALTK402	30 TAC Chapter 115, Storage of VOCs	R5112-5A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Control Device Type = Flare	
EALTK402	30 TAC Chapter 115, Storage of VOCs	R5112-5B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK402	30 TAC Chapter 115, Storage of VOCs	R5112-5C	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK402	30 TAC Chapter 115, Storage of VOCs	R5112-5D	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK402	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Designated HAL = The emission stream is not designated as halogenated.</p> <p>Emission Standard = HAP vapor pressure is greater than or equal to 76.6 and a flare is being used for control per • 63.2470(a)- Table 4.1.a.ii.</p> <p>Determined HAL = The emission stream is determined not to be halogenated.</p> <p>Prior Eval = The data from a prior evaluation or assessment is not being used.</p> <p>Assessment Waiver = The Administrator has granted a waiver of compliance assessment.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p>	
EALTK7	30 TAC Chapter 115, Storage of VOCs	R5112-4A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK7	30 TAC Chapter 115, Storage of VOCs	R5112-4B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK7	30 TAC Chapter 115, Storage of VOCs	R5112-4C	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>	
EALTK7	30 TAC Chapter 115, Storage of VOCs	R5112-4D	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK7	30 TAC Chapter 115, Storage of VOCs	R5112-4E	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EALTK8	30 TAC Chapter 115, Storage of VOCs	R5112-4A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EALTK8	30 TAC Chapter 115, Storage of VOCs	R5112-4B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EALTK8	30 TAC Chapter 115, Storage of VOCs	R5112-4C	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit	
EALTK8	30 TAC Chapter 115, Storage of VOCs	R5112-4D	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EALTK8	30 TAC Chapter 115, Storage of VOCs	R5112-4E	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EBGTK6901	40 CFR Part 60, Subpart K	60K-1	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less Product Stored = Stored product other than petroleum liquid (as defined in 40 CFR Part 60, Subpart K)	
EBGTK6902	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
EBGTK6902	40 CFR Part 60, Subpart K	60K-2	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less Product Stored = Stored product other than petroleum liquid (as defined in 40 CFR Part 60, Subpart K)	
EBGTK6904	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
EBGTK6905	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 40,000 gallons	
EBGTK6905	40 CFR Part 60, Subpart Ka	60KA-1	Product Stored = Stored product other than a petroleum liquid	
EBGTK6905	40 CFR Part 61, Subpart FF	61FF-3	Waste Treatment Tank = The tank does not manage, treat or store a waste stream subject to 40 CFR Part 61, Subpart FF.	
EC4DM21	30 TAC Chapter 115, Storage of VOCs	R5112-1A	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Control Device Type = Flare	
EC4DM21	30 TAC Chapter 115, Storage of VOCs	R5112-1B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4DM21	30 TAC Chapter 115, Storage of VOCs	R5112-1C	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>	
EC4DM21	30 TAC Chapter 115, Storage of VOCs	R5112-1D	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4DM21	30 TAC Chapter 115, Storage of VOCs	R5112-1E	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4DM21	40 CFR Part 63, Subpart G	63G-1B	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM21	40 CFR Part 63, Subpart G	63G-1C	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>	
EC4DM21	40 CFR Part 63, Subpart G	63G-1D	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM21	40 CFR Part 63, Subpart G	63G-1E	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM3075	30 TAC Chapter 115, Storage of VOCs	R5112-2A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4DM3075	30 TAC Chapter 115, Storage of VOCs	R5112-2B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4DM3075	30 TAC Chapter 115, Storage of VOCs	R5112-2C	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4DM3075	30 TAC Chapter 115, Storage of VOCs	R5112-2D	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4DM3075	40 CFR Part 63, Subpart G	63G-1A	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM3075	40 CFR Part 63, Subpart G	63G-1B	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM3075	40 CFR Part 63, Subpart G	63G-1C	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM3075	40 CFR Part 63, Subpart G	63G-1D	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM3075	40 CFR Part 63, Subpart G	63G-1E	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM3075	40 CFR Part 63, Subpart G	63G-1F	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM3075	40 CFR Part 63, Subpart G	63G-1G	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM3075	40 CFR Part 63, Subpart G	63G-1H	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4DM59	30 TAC Chapter 115, Storage of VOCs	R5112-10A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4DM59	30 TAC Chapter 115, Storage of VOCs	R5112-10B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EC4DM59	40 CFR Part 63, Subpart G	63G-10A	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Control Device Type = Flare Emission Control Type = Closed vent system (CVS) and control device (fixed roof)	
EC4DM59	40 CFR Part 63, Subpart G	63G-10B	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Control Device Type = Flare Emission Control Type = Closed vent system (CVS) and control device (fixed roof)	
EC4DM59	40 CFR Part 63, Subpart G	63G-10C	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Control Device Type = Flare Emission Control Type = Closed vent system (CVS) and control device (fixed roof)	
EC4DM59	40 CFR Part 63, Subpart G	63G-10D	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			(76.6 kPa) Control Device Type = Flare Emission Control Type = Closed vent system (CVS) and control device (fixed roof)	
EC4TK3941	30 TAC Chapter 115, Storage of VOCs	R5112-10A	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EC4TK3941	30 TAC Chapter 115, Storage of VOCs	R5112-10B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EC4TK3941	40 CFR Part 63, Subpart G	63G-5A	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Control Device Type = Flare Emission Control Type = Closed vent system (CVS) and control device (fixed roof)	
EC4TK3941	40 CFR Part 63, Subpart G	63G-5B	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Control Device Type = Flare Emission Control Type = Closed vent system (CVS) and control device (fixed roof)	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EC4TK3942	30 TAC Chapter 115, Storage of VOCs	R5112-10A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4TK3942	30 TAC Chapter 115, Storage of VOCs	R5112-10B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC4TK3942	40 CFR Part 63, Subpart G	63G-5A	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC4TK3942	40 CFR Part 63, Subpart G	63G-5B	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EC5DM56	30 TAC Chapter 115, Storage of VOCs	R5112-1A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Flare	
EC5DM56	30 TAC Chapter 115, Storage of VOCs	R5112-1B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Flare	
EC5TK21	30 TAC Chapter 115, Storage of VOCs	R5112-2A	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EC5TK21	30 TAC Chapter 115, Storage of VOCs	R5112-2B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EC5TK27	30 TAC Chapter 115, Storage of VOCs	R5112-1	Tank Description = Tank using a submerged fill pipe Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 40,000 gallons	
EC5TK30	30 TAC Chapter 115, Storage of VOCs	R5112-1	Tank Description = Tank using a submerged fill pipe Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 40,000 gallons	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EC5TK31	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
EC5TK3116	30 TAC Chapter 115, Storage of VOCs	R5112-3	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EC5TK317	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
EC5TK36	30 TAC Chapter 115, Storage of VOCs	R5112-5	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
EC5TK36	30 TAC Chapter 115, Storage of VOCs	R5112-5B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
EMTTK12	30 TAC Chapter 115, Storage of VOCs	R5112-3A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EMTTK12	30 TAC Chapter 115, Storage of VOCs	R5112-3B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EMTTK12	30 TAC Chapter 115, Storage of VOCs	R5112-3C	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit	
EMTTK12	30 TAC Chapter 115, Storage of VOCs	R5112-3D	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EMTTK12	30 TAC Chapter 115, Storage of VOCs	R5112-3E	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EMTTK18	30 TAC Chapter 115, Storage of VOCs	R5112-4A	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EMTTK18	30 TAC Chapter 115, Storage of VOCs	R5112-4B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EMTTK18	30 TAC Chapter 115, Storage of VOCs	R5112-4C	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>	
EMTTK18	30 TAC Chapter 115, Storage of VOCs	R5112-4D	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EMTTK18	30 TAC Chapter 115, Storage of VOCs	R5112-4E	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EMTTK19	30 TAC Chapter 115, Storage of VOCs	R5112-5A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EMTTK19	30 TAC Chapter 115, Storage of VOCs	R5112-5B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EMTTK19	30 TAC Chapter 115, Storage of VOCs	R5112-5C	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit	
EMTTK19	30 TAC Chapter 115, Storage of VOCs	R5112-5D	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EMTTK19	30 TAC Chapter 115, Storage of VOCs	R5112-5E	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
EMTTK26	30 TAC Chapter 115, Storage of	R5112-7	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		<p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
EMTTK26	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Two seals, one located above the other, the primary seal being a metallic shoe seal</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p>	
EMTTK4	30 TAC Chapter 115, Storage of VOCs	R5112-9A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EMTTK4	30 TAC Chapter 115, Storage of VOCs	R5112-9B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EMTTK4	30 TAC Chapter 115, Storage of VOCs	R5112-9C	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EMTTK4	30 TAC Chapter 115, Storage of VOCs	R5112-9D	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EMTTK4	40 CFR Part 63, Subpart G	63G-9A	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EMTTK4	40 CFR Part 63, Subpart G	63G-9B	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EMTTK4	40 CFR Part 63, Subpart G	63G-9C	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EMTTK4	40 CFR Part 63,	63G-9D	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart G		<p>new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
EMTTK47	30 TAC Chapter 115, Storage of VOCs	R5112-13	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
EMTTK47	40 CFR Part 63, Subpart G	63G-1	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>Emission Control Type = Fixed-roof tank equipped with an internal floating roof that meets the requirements specified in 40 CFR § 63.119(b)</p> <p>New Source = The source is an existing source.</p>	
EMTTK47	40 CFR Part 63, Subpart G	63G-9	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
EMTTK5	30 TAC Chapter 115, Storage of VOCs	R5112-10A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EMTTK5	30 TAC Chapter 115, Storage of VOCs	R5112-10B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EMTTK5	30 TAC Chapter 115, Storage of VOCs	R5112-10C	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>	
EMTTK5	30 TAC Chapter 115, Storage of VOCs	R5112-10D	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EMTTK5	30 TAC Chapter 115, Storage of VOCs	R5112-10E	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
EUTDM01086	40 CFR Part 60, Subpart Kb	60Kb-39A	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 2.2 psia but less than 4.0 psia</p> <p>Storage Vessel Description = Emission controls not required (fixed roof)</p>	
EUTDM01086	40 CFR Part 60,	60Kb-39C	Product Stored = Volatile organic liquid	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	
EUTDM01086	40 CFR Part 60, Subpart Kb	60Kb-39E	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 4.0 psia but less than 11.1 psia Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)	
EUTDM01086	40 CFR Part 60, Subpart Kb	60Kb-39F	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 4.0 psia but less than 11.1 psia Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)	
EUTDM01086	40 CFR Part 61, Subpart FF	61FF-18A	Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device. Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device. Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351. Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system. Control Device Type/Operations = Flare Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3). Closed Vent System and Control Device AMOC = Not using an alternate means of compliance Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.	
EUTDM01086	40 CFR Part 61, Subpart FF	61FF-18B	Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device. Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device. Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351. Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system. Control Device Type/Operations = Flare Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
EUTDM01086	40 CFR Part 63, Subpart G	63G-28A	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is greater than 75m³ but less than 151m³ and vapor pressure of liquid stored is less than 13.1 kPa</p>	
EUTDM01086	40 CFR Part 63, Subpart G	63G-28B	<p>Negative Pressure = The fixed roof and closed vent systems are not operated and maintained under negative pressure.</p> <p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>By-pass Lines = Closed vent system has no by-pass lines</p> <p>Emission Control Type = Fixed roof tank vented through a closed vent system that routes the organic HAP vapors vented from the wastewater tank to a control device</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Control Device Type = Flare</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.</p>	
EUTDM01086	40 CFR Part 63, Subpart G	63G-28C	<p>Negative Pressure = The fixed roof and closed vent systems are not operated and maintained under negative pressure.</p> <p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>By-pass Lines = Closed vent system has no by-pass lines</p> <p>Emission Control Type = Fixed roof tank vented through a closed vent system that routes the organic HAP vapors vented from the wastewater tank to a control device</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Control Device Type = Flare</p> <p>New Source = The source is an existing source.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.	
EUTTK1101A	40 CFR Part 61, Subpart FF	61FF-1A	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
EUTTK1101B	40 CFR Part 61, Subpart FF	61FF-1A	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
EUTTK88014	40 CFR Part 60, Subpart Kb	60Kb-39A	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia</p> <p>Storage Vessel Description = Emission controls not required (fixed roof)</p>	
EUTTK88014	40 CFR Part 60, Subpart Kb	60Kb-39B	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EUTTK88014	40 CFR Part 60, Subpart Kb	60Kb-39C	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)</p>	
EUTTK88014	40 CFR Part 60, Subpart Kb	60Kb-39D	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)</p>	
EUTTK88014	40 CFR Part 61, Subpart FF	61FF-18A	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
EUTTK88014	40 CFR Part 61, Subpart FF	61FF-18B	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
EUTTK88014	40 CFR Part 63, Subpart G	63G-28A	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank greater than or equal to 151m3 and vapor pressure of liquid stored is less than 5.2 kPa</p>	
EUTTK88014	40 CFR Part 63, Subpart G	63G-28B	<p>Negative Pressure = The fixed roof and closed vent systems are not operated and maintained under negative pressure.</p> <p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>By-pass Lines = Closed vent system has no by-pass lines</p> <p>Emission Control Type = Fixed roof tank vented through a closed vent system that routes the organic HAP vapors vented from the wastewater tank to a control device</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Control Device Type = Flare</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.</p>	
EUTTK88014	40 CFR Part 63, Subpart G	63G-28C	<p>Negative Pressure = The fixed roof and closed vent systems are not operated and maintained under negative pressure.</p> <p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>By-pass Lines = Closed vent system has no by-pass lines</p> <p>Emission Control Type = Fixed roof tank vented through a closed vent system that routes the organic HAP vapors vented from the wastewater tank to a control device</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Control Device Type = Flare</p> <p>New Source = The source is an existing source.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters for the control device have not been requested or approved.</p>	
GRPBTBZTK	30 TAC Chapter 115, Storage of VOCs	R5112-3	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPBTBZTK	40 CFR Part 63, Subpart G	63G-3	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
GRPC4MTTK1	30 TAC Chapter 115, Storage of VOCs	R5112-4A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
GRPC4MTTK1	30 TAC Chapter 115, Storage of VOCs	R5112-4B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
GRPC4MTTK1	30 TAC Chapter 115, Storage of VOCs	R5112-4C	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>	
GRPC4MTTK1	30 TAC Chapter 115, Storage of VOCs	R5112-4D	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
GRPC4MTTK1	30 TAC Chapter 115, Storage of VOCs	R5112-4E	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
GRPC4MTTK1	40 CFR Part 63, Subpart G	63G-1A	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
GRPC4MTTK1	40 CFR Part 63, Subpart G	63G-1B	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
GRPC4MTTK1	40 CFR Part 63, Subpart G	63G-1C	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>	
GRPC4MTTK1	40 CFR Part 63, Subpart G	63G-1D	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>	
GRPC4MTTK1	40 CFR Part 63, Subpart G	63G-1E	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
GRPC4MTTK1	40 CFR Part 63, Subpart G	63G-1F	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
GRPC5TK1	30 TAC Chapter 115, Storage of VOCs	R5112-4A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
GRPC5TK1	30 TAC Chapter 115, Storage of VOCs	R5112-4B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
GRPC5TK2	30 TAC Chapter 115, Storage of VOCs	R5112-4A	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons Control Device Type = Flare	
GRPC5TK2	30 TAC Chapter 115, Storage of VOCs	R5112-4B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons Control Device Type = Flare	
GRPC5TK2	40 CFR Part 63, Subpart FFFF	63FFFF-1	Designated HAL = The emission stream is not designated as halogenated. Determined HAL = The emission stream is determined not to be halogenated. Emission Standard = HAP vapor pressure is less than 76.6 and a flare is being used for control per § 63.2470(a)-Table 4.1.b.iii. Determined HAL = The emission stream is determined not to be halogenated. HAL Device Type = No halogen scrubber or other halogen reduction device is used. Prior Eval = The data from a prior evaluation or assessment is not being used. Prior Test = The data from a prior performance test is not used. Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or a waiver was not requested. Test Waiver = The Administrator has not granted a waiver of the performance test or no waiver has been requested.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Formaldehyde = The stream does not contain formaldehyde.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p>	
GRPECUDM	30 TAC Chapter 115, Storage of VOCs	R5112-1A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
GRPECUDM	30 TAC Chapter 115, Storage of VOCs	R5112-1B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
GRPECUDM	40 CFR Part 60, Subpart Kb	60Kb-1A	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)</p>	
GRPECUDM	40 CFR Part 60, Subpart Kb	60Kb-1B	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)</p>	
GRPECUDM	40 CFR Part 60, Subpart Kb	60Kb-1C	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 11.1 psia</p> <p>Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)</p>	
GRPECUDM	40 CFR Part 60,	60Kb-1D	Product Stored = Volatile organic liquid	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart Kb		<p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 11.1 psia</p> <p>Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)</p>	
GRPECUDM	40 CFR Part 61, Subpart FF	61FF-1A	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Closed Vent System and Control Device = No closed vent system and control device is used.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
GRPECUDM	40 CFR Part 61, Subpart FF	61FF-1B	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Closed Vent System and Control Device = No closed vent system and control device is used.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
GRPECUDM	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Designated HAL = The emission stream is not designated as halogenated.</p> <p>Emission Standard = HAP vapor pressure is greater than or equal to 76.6 and a flare is being used for control per • 63.2470(a)- Table 4.1.a.ii.</p> <p>Determined HAL = The emission stream is determined not to be halogenated.</p> <p>Prior Eval = The data from a prior evaluation or assessment is not being used.</p> <p>Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or a waiver was not</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>requested.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p>	
GRPMEOTK	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPMEOTK	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
GRPMTTK1	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPMTTK1	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
GRPMTTK2	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPMTTK2	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
GRPOLTGHVY	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPOLTGHVY	40 CFR Part 63, Subpart YY	63YY-1	<p>Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.</p>	
GRPOLTKIFR	30 TAC Chapter 115, Storage of VOCs	R5112-3	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPOLTKIFR	40 CFR Part 60, Subpart K	60K-3A	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Petroleum (other than crude oil) or condensate</p> <p>True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia</p> <p>Storage Vessel Description = Floating roof (internal or external)</p> <p>Reid Vapor Pressure = Reid vapor pressure not determined</p>	
GRPOLTKIFR	40 CFR Part 60, Subpart K	60K-3B	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Storage Vessel Description = Floating roof (internal or external)</p> <p>Reid Vapor Pressure = Reid vapor pressure not determined</p> <p>Maximum True Vapor Pressure = Maximum true vapor pressure is 1.0 psia or less</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPOLTIFR	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
GRPOP1TK1	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Welded tank using an external floating roof Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Primary Seal = Mechanical shoe Storage Capacity = Capacity is greater than 40,000 gallons Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized	
GRPOP1TK1	40 CFR Part 60, Subpart K	60K-1A	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters) Product Stored = Petroleum (other than crude oil) or condensate True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure not determined	
GRPOP1TK1	40 CFR Part 60, Subpart K	60K-1B	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters) Product Stored = Petroleum liquid (other than petroleum or condensate) True Vapor Pressure = True vapor pressure is less than 1.5 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure not determined Maximum True Vapor Pressure = Maximum true vapor pressure is 1.0 psia or less	
GRPOP1TK1	40 CFR Part 61, Subpart FF	61FF-17	Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351. Kb Tank Type = Using an external floating roof that meets the requirements of 40 CFR § 60.112b(a)(2) Seal Type = Mechanical shoe primary seal	
GRPOP1TK1	40 CFR Part 63, Subpart G	63G-27	Process Wastewater = The tank receives, manages, or treats process wastewater streams Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged. Wastewater Tank Properties = Properties do not qualify for exemption Emission Control Type = External floating roof that meets the requirements specified in 40 CFR § 63.119(c), 40 CFR § 63.120(b)(5), and 40 CFR § 63.120(b)(6)	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			New Source = The source is an existing source.	
GRPOP1TK1	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
GRPOP1TK5	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
GRPOP1TK5	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
GRPOP1TK6	40 CFR Part 60, Subpart Kb	60Kb-3A	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia Storage Vessel Description = Emission controls not required (fixed roof)	
GRPOP1TK6	40 CFR Part 60, Subpart Kb	60Kb-3B	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal	
GRPOP1TK6	40 CFR Part 61, Subpart FF	61FF-4	Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351. Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1) Seal Type = Mechanical shoe seal	
GRPOP1TK6	40 CFR Part 63, Subpart FFFF	63FFFF-1	Process Wastewater = Tank receives, manages or treats process wastewater as defined in 40 CFR Part 63, Subpart F and 40 CFR § 63.2485(b). Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank sparged. Wastewater Tank Properties = Volume of the wastewater tank greater than or equal to 151 m ³ and vapor pressure of liquid stored is less than 5.2 kPa.	
GRPOP1TK6	40 CFR Part 63, Subpart G	63G-4	Process Wastewater = The tank receives, manages, or treats process wastewater streams Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>Emission Control Type = Fixed-roof tank equipped with an internal floating roof that meets the requirements specified in 40 CFR § 63.119(b)</p> <p>New Source = The source is an existing source.</p>	
GRPOP1TK6	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
GRPOP2TK1	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
GRPOP2TK1	40 CFR Part 60, Subpart K	60K-1B	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Storage Vessel Description = Floating roof (internal or external)</p> <p>Reid Vapor Pressure = Reid vapor pressure not determined</p> <p>Maximum True Vapor Pressure = Maximum true vapor pressure is 1.0 psia or less</p>	
GRPOP2TK1	40 CFR Part 60, Subpart K	60K-2A	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Petroleum (other than crude oil) or condensate</p> <p>True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia</p> <p>Storage Vessel Description = Floating roof (internal or external)</p> <p>Reid Vapor Pressure = Reid vapor pressure not determined</p>	
GRPOP2TK1	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
GRPOP2TK2	30 TAC Chapter 115, Storage of VOCs	R5112-5	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
GRPOP2TK2	40 CFR Part 63, Subpart G	63G-2	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
GRPOP2TK5	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
GRPOP2TK5	40 CFR Part 63, Subpart YY	63YY-1	<p>Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.</p>	
GRPOP2TK6	40 CFR Part 60, Subpart Kb	60Kb-8	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
GRPOP2TK6	40 CFR Part 61, Subpart FF	61FF-5	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p>	
GRPOP2TK6	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Process Wastewater = Tank receives, manages or treats process wastewater as defined in 40 CFR Part 63, Subpart F and 40 CFR § 63.2485(b).</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank greater than or equal to 151 m³ and vapor pressure of liquid stored is less than 5.2 kPa.</p>	
GRPOP2TK6	40 CFR Part 63, Subpart G	63G-11	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75m³ and storing liquid with any vapor pressure</p>	
GRPOP2TK6	40 CFR Part 63, Subpart G	63G-7	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Properties do not qualify for exemption</p> <p>Emission Control Type = Fixed-roof tank equipped with an internal floating roof that meets the requirements specified in 40 CFR § 63.119(b)</p> <p>New Source = The source is an existing source.</p>	
GRPOP2TK6	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
GRPOP2TK7	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
GRPSMLTANK	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
GRPSMLTANK	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
GRPSMLTANK	40 CFR Part 60, Subpart Kb	60Kb-E	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
GRPTKNOAPP	30 TAC Chapter 115, Storage of VOCs	R5112-E	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is less than or equal to 1,000 gallons</p>	
GRPTKNOAPP	40 CFR Part 60,	60Kb-E	Product Stored = Volatile organic liquid	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
MBTDM4009	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MBTDM4009	40 CFR Part 63, Subpart G	63G-10	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	
MBTTK3112	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
MBTTK3112	40 CFR Part 63, Subpart G	63G-2	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Two seals, one located above the other, the primary seal being a metallic shoe seal</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p>	
MBTTK3113	30 TAC Chapter 115, Storage of VOCs	R5112-4	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MBTTK3113	40 CFR Part 63, Subpart G	63G-4	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
MBTTK3114	30 TAC Chapter 115, Storage of VOCs	R5112-6	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MBTTK3114	40 CFR Part 63, Subpart G	63G-6	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
MBTTK3115	30 TAC Chapter 115, Storage of VOCs	R5112-5	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
MBTTK3115	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i.</p> <p>WW Tank Control = An external floating roof is operated and maintained per 40 CFR § 63.1062(a)(2).</p> <p>Notification = The referencing subpart requires notification of initial startup.</p> <p>Unslotted Guide Pole = The tank does not use an unslotted guide pole.</p> <p>Wiper or Seal = The wiper or seal of the unslotted guide pole is at or above the pole wiper.</p> <p>Seal Configuration = Mechanical shoe primary seal and a secondary seal.</p>	
MBTTK3115	40 CFR Part 63, Subpart G	63G-2	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Seal Type = Two seals, one located above the other, the primary seal being a metallic shoe seal NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = External floating roof	
MBTTK4002	30 TAC Chapter 115, Storage of VOCs	R5112-1	Tank Description = Tank using a submerged fill pipe Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 40,000 gallons	
MBTTK4002	40 CFR Part 63, Subpart G	63G-6	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	
MBTTK4003	30 TAC Chapter 115, Storage of VOCs	R5112-1	Tank Description = Tank using a submerged fill pipe Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
MBTTK4003	40 CFR Part 63, Subpart G	63G-7	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	
MBTTK4004	30 TAC Chapter 115, Storage of VOCs	R5112-1	Tank Description = Tank using a submerged fill pipe Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
MBTTK4004	40 CFR Part 63, Subpart G	63G-8	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	
MBTTK4011	30 TAC Chapter 115, Storage of VOCs	R5112-1	Tank Description = Tank does not require emission controls Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
MEOSP7045	30 TAC Chapter 115, Storage of	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		<p>compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MIPTK2615	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MIPTK2615	40 CFR Part 60, Subpart Kb	60Kb-3	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p> <p>Storage Vessel Description = Emission controls not required (fixed roof)</p>	
MIPTK2615	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i.</p> <p>WW Tank Control = An internal floating roof is operated and maintained per 40 CFR § 63.1062(a)(1).</p> <p>Notification = The referencing subpart requires notification of initial startup.</p> <p>Unslotted Guide Pole = The tank uses an unslotted guide pole.</p> <p>Wiper or Seal = The unslotted guide pole is equipped with a pole wiper and a pole sleeve.</p> <p>Seal Configuration = Mechanical shoe seal.</p>	
MIPTK3105	30 TAC Chapter 115, Storage of VOCs	R5112-3	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MIPTK3105	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i.</p> <p>WW Tank Control = An internal floating roof is operated and maintained per 40 CFR § 63.1062(a)(1).</p> <p>Notification = The referencing subpart requires notification of initial startup.</p> <p>Unslotted Guide Pole = The tank does not use an unslotted guide pole.</p> <p>Wiper or Seal = The wiper or seal of the unslotted guide pole is at or above the pole wiper.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Seal Configuration = Mechanical shoe seal.	
MIPTK3106	30 TAC Chapter 115, Storage of VOCs	R5112-4	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MIPTK3107	30 TAC Chapter 115, Storage of VOCs	R5112-5	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MIPTK3108	30 TAC Chapter 115, Storage of VOCs	R5112-6	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MIPTK3109	30 TAC Chapter 115, Storage of VOCs	R5112-7	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MIPTK3110	30 TAC Chapter 115, Storage of VOCs	R5112-4	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MIPTK3110	40 CFR Part 61, Subpart FF	61FF-1	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1) Seal Type = Mechanical shoe seal	
MIPTK3110	40 CFR Part 63, Subpart FFFF	63FFFF-1	Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i. WW Tank Control = An internal floating roof is operated and maintained per 40 CFR § 63.1062(a)(1). Notification = The referencing subpart requires notification of initial startup. Unslotted Guide Pole = The tank does not use an unslotted guide pole. Wiper or Seal = The wiper or seal of the unslotted guide pole is at or above the pole wiper. Seal Configuration = Mechanical shoe seal.	
MIPTK3123	30 TAC Chapter 115, Storage of VOCs	R5112-7	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	
MIPTK3123	40 CFR Part 63, Subpart G	63G-1	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111) NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Internal floating roof	
MIPTK3124	30 TAC Chapter 115, Storage of VOCs	R5112-7	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	
MIPTK3124	40 CFR Part 63, Subpart G	63G-1	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111) NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Internal floating roof	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
MPBDM3219	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3205	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3207	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3208	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3209	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3210	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3211	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MPBTK3212	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3213	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MPBTK3214	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3215	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
MPBTK3216	30 TAC Chapter 115, Storage of	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		<p>compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3217	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3218	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3219	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3221	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3224	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
MPBTK3233X	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MPBTK3233X	40 CFR Part 60, Subpart Kb	60Kb-1	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
MPBTRAILER	30 TAC Chapter 115, Storage of VOCs	R5112-16	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Flare</p>	
MSMDM2801	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MSMDM2802	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MSMTK2801	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
MSMTK2802	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MSMTK2803	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
MSMTK2811	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OFXDM4310	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OFXDM4310	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OFXDM4311	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OFXDM4311	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OFXDM4383	30 TAC Chapter 115, Storage of VOCs	R5112-8A	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Flare	
OFXDM4383	30 TAC Chapter 115, Storage of VOCs	R5112-8B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Flare	
OFXDM4383	40 CFR Part 61, Subpart FF	61FF-1A	Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device. Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device. Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351. Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system. Control Device Type/Operations = Flare Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3). Closed Vent System and Control Device AMOC = Not using an alternate means of compliance Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.	
OFXDM4383	40 CFR Part 61, Subpart FF	61FF-1B	Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device. Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device. Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351. Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1DM3904	30 TAC Chapter 115, Storage of VOCs	R5112-24A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Flare</p>	
OP1DM3904	30 TAC Chapter 115, Storage of VOCs	R5112-24B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p> <p>Control Device Type = Flare</p>	
OP1SP3902	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OP1SU3406	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3406	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3406	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3406	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3407	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3407	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3407	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.	
OP1SU3407	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3407	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Process Wastewater = Tank receives, manages or treats process wastewater as defined in 40 CFR Part 63, Subpart F and 40 CFR § 63.2485(b).</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75 m³ and storing liquid with any vapor pressure,</p>	
OP1SU3407	40 CFR Part 63, Subpart G	63G-11	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75m³ and storing liquid with any vapor pressure</p>	
OP1SU3407	40 CFR Part 63, Subpart G	63G-12	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75m³ and storing liquid with any vapor pressure</p>	
OP1SU3502	40 CFR Part 61,	61FF-6	Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart FF		<p>device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3502	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3502	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3502	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3671	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3671	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3671	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU3671	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU38099	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU38099	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU38099	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1SU38099	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1TK3406	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OP1TK3406	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1TK3406	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1TK3406	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1TK3406	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1TK3451	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
OP1TK3455	40 CFR Part 60, Subpart Kb	60Kb-1	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal	
OP1TK3455	40 CFR Part 61, Subpart FF	61FF-5	Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351. Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1) Seal Type = Mechanical shoe seal	
OP1TK3455	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP1TK3458	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
OP1TK3458	40 CFR Part 61, Subpart FF	61FF-6	Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device. Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device. Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351. Bypass Line Valve = A flow indicator is used to monitor the by-pass line. Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system. Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3). Closed Vent System and Control Device AMOC = Not using an alternate means of compliance Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation. Alternate Monitoring Parameters = Alternate monitoring parameters not requested Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.	
OP1TK3458	40 CFR Part 61, Subpart FF	61FF-7	Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device. Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1TK3458	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1TK3458	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP1TK3601	30 TAC Chapter 115, Storage of VOCs	R5112-6	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OP1TK3601	30 TAC Chapter 115, Storage of VOCs	R5112-6B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OP1TK38008	40 CFR Part 61, Subpart FF	61FF-2	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p>	
OP1TK38008	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Process Wastewater = Tank receives, manages or treats process wastewater as defined in 40 CFR Part 63, Subpart F and 40 CFR § 63.2485(b).</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75 m³ and storing liquid with any vapor pressure,</p>	
OP1TK38008	40 CFR Part 63,	63G-2	Process Wastewater = The tank receives, manages, or treats process wastewater streams	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart G		<p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75m³ and storing liquid with any vapor pressure</p>	
OP1TK38008	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP1TK38009	40 CFR Part 61, Subpart FF	61FF-3	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p>	
OP1TK38009	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Process Wastewater = Tank receives, manages or treats process wastewater as defined in 40 CFR Part 63, Subpart F and 40 CFR § 63.2485(b).</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75 m³ and storing liquid with any vapor pressure,</p>	
OP1TK38009	40 CFR Part 63, Subpart G	63G-3	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75m³ and storing liquid with any vapor pressure</p>	
OP1TK38009	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP1TK38303	30 TAC Chapter 115, Storage of VOCs	R5112-12	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
OP1TK38303	30 TAC Chapter 115, Storage of VOCs	R5112-12A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 40,000 gallons	
OP1TK3903	40 CFR Part 60, Subpart Kb	60Kb-E1	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	
OP1TK3903	40 CFR Part 60, Subpart Kb	60Kb-E2	Product Stored = Stored product other than volatile organic liquid or petroleum liquid	
OP1TK3908	30 TAC Chapter 115, Storage of VOCs	R5112-7A	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
OP1TK3908	30 TAC Chapter 115, Storage of VOCs	R5112-7B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
OP1TK3909	30 TAC Chapter 115, Storage of VOCs	R5112-8A	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Flare	
OP1TK3909	30 TAC Chapter 115, Storage of VOCs	R5112-8B	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Control Device Type = Flare	
OP1TK3910	30 TAC Chapter 115, Storage of VOCs	R5112-9A	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
OP1TK3910	30 TAC Chapter 115, Storage of VOCs	R5112-9B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
OP1TK3911	30 TAC Chapter 115, Storage of VOCs	R5112-4	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
OP1TK3911	40 CFR Part 60, Subpart K	60K-4	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia</p> <p>Storage Vessel Description = Floating roof (internal or external)</p> <p>Reid Vapor Pressure = Reid vapor pressure not determined</p>	
OP1TK3911	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP1TK3912	30 TAC Chapter 115, Storage of	R5112-4	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		<p>compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
OP1TK3912	40 CFR Part 60, Subpart K	60K-5	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia</p> <p>Storage Vessel Description = Floating roof (internal or external)</p> <p>Reid Vapor Pressure = Reid vapor pressure not determined</p>	
OP1TK3912	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i.</p> <p>WW Tank Control = An external floating roof is operated and maintained per 40 CFR § 63.1062(a)(2).</p> <p>Notification = The referencing subpart requires notification of initial startup.</p> <p>Unslotted Guide Pole = The tank does not use an unslotted guide pole.</p> <p>Wiper or Seal = The wiper or seal of the unslotted guide pole is at or above the pole wiper.</p> <p>Seal Configuration = Mechanical shoe primary seal and a secondary seal.</p>	
OP2SU4406	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4406	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4406	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			40 CFR § 61.343 for tanks.	
OP2SU4406	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4406	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP2SU4407	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			40 CFR § 61.343 for tanks.	
OP2SU4407	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4407	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4407	40 CFR Part 61,	61FF-9	Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart FF		<p>device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4407	40 CFR Part 63, Subpart G	63G-10	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75m³ and storing liquid with any vapor pressure</p>	
OP2SU4407	40 CFR Part 63, Subpart G	63G-12	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75m³ and storing liquid with any vapor pressure</p>	
OP2SU4407	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP2SU4502	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4502	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4502	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4502	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4671	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4671	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU4671	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU48099	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU48099	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			40 CFR § 61.343 for tanks.	
OP2SU48099	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU48099	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2SU48099	40 CFR Part 63,	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart YY		Table 7 to be subject to § 63.1103.	
OP2TK4451	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
OP2TK4455	40 CFR Part 60, Subpart Kb	60Kb-3	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
OP2TK4455	40 CFR Part 61, Subpart FF	61FF-2	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p>	
OP2TK4455	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP2TK4456	30 TAC Chapter 115, Storage of VOCs	R5112-10	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OP2TK4458	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OP2TK4458	40 CFR Part 61, Subpart FF	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2TK4458	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2TK4458	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2TK4458	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2TK4465	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OP2TK4465	40 CFR Part 61,	61FF-6	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart FF		<p>device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2TK4465	40 CFR Part 61, Subpart FF	61FF-7	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2TK4465	40 CFR Part 61, Subpart FF	61FF-8	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and with a reduction of organics being greater than or equal to 95 weight percent</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2TK4465	40 CFR Part 61, Subpart FF	61FF-9	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Boiler or process heater having a design heat input capacity greater than or equal to 44 MW and that achieves a total organic compound concentration of 20 ppmv on a dry basis corrected to 3% oxygen</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
OP2TK4601	30 TAC Chapter 115, Storage of VOCs	R5112-9	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP2TK4601	30 TAC Chapter 115, Storage of VOCs	R5112-9B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OP2TK48007	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
OP2TK48007	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP2TK48008	40 CFR Part 61, Subpart FF	61FF-2	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p>	
OP2TK48008	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Process Wastewater = Tank receives, manages or treats process wastewater as defined in 40 CFR Part 63, Subpart F and 40 CFR § 63.2485(b).</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75 m³ and storing liquid with any vapor pressure,</p>	
OP2TK48008	40 CFR Part 63, Subpart G	63G-1	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75m³ and storing liquid with any vapor pressure</p>	
OP2TK48008	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP2TK48009	40 CFR Part 61, Subpart FF	61FF-3	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Seal Type = Mechanical shoe seal	
OP2TK48009	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Process Wastewater = Tank receives, manages or treats process wastewater as defined in 40 CFR Part 63, Subpart F and 40 CFR § 63.2485(b).</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75 m³ and storing liquid with any vapor pressure,</p>	
OP2TK48009	40 CFR Part 63, Subpart G	63G-1	<p>Process Wastewater = The tank receives, manages, or treats process wastewater streams</p> <p>Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged.</p> <p>Wastewater Tank Properties = Volume of the wastewater tank is less than 75m³ and storing liquid with any vapor pressure</p>	
OP2TK48009	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP2TK48105	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
OP2TK48303	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
OP2TK48303	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP2TK4901	30 TAC Chapter 115, Storage of VOCs	R5112-1B	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 40,000 gallons Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized	
OP2TK4901	40 CFR Part 60, Subpart K	60K-1A	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters) Product Stored = Petroleum (other than crude oil) or condensate True Vapor Pressure = True vapor pressure is less than 1.5 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure not determined Maximum True Vapor Pressure = Maximum true vapor pressure is 1.0 psia or less	
OP2TK4901	40 CFR Part 60, Subpart K	60K-1B	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters) Product Stored = Petroleum liquid (other than petroleum or condensate) True Vapor Pressure = True vapor pressure is less than 1.5 psia Storage Vessel Description = Floating roof (internal or external) Reid Vapor Pressure = Reid vapor pressure not determined Maximum True Vapor Pressure = Maximum true vapor pressure is 1.0 psia or less	
OP2TK4901	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.	
OP2TK4915	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is less than 1.0 psia Storage Capacity = Capacity is greater than 40,000 gallons	
OP2TK4916	30 TAC Chapter 115, Storage of VOCs	R5112-4	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof (IFR) Product Stored = VOC other than crude oil or condensate True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Storage Capacity = Capacity is greater than 40,000 gallons	
OP2TK4916	40 CFR Part 63, Subpart G	63G-1	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
OP2TK4921	30 TAC Chapter 115, Storage of VOCs	R5112-12	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
OP2TK4921	40 CFR Part 60, Subpart K	60K-4A	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Petroleum (other than crude oil) or condensate</p> <p>True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia</p> <p>Storage Vessel Description = Floating roof (internal or external)</p> <p>Reid Vapor Pressure = Reid vapor pressure not determined</p>	
OP2TK4921	40 CFR Part 60, Subpart K	60K-4B	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is greater than 65,000 gallons (246,052 liters)</p> <p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Storage Vessel Description = Floating roof (internal or external)</p> <p>Reid Vapor Pressure = Reid vapor pressure not determined</p> <p>Maximum True Vapor Pressure = Maximum true vapor pressure is 1.0 psia or less</p>	
OP2TK4921	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i.</p> <p>WW Tank Control = An external floating roof is operated and maintained per 40 CFR § 63.1062(a)(2).</p> <p>Notification = The referencing subpart requires notification of initial startup.</p> <p>Unslotted Guide Pole = The tank does not use an unslotted guide pole.</p> <p>Wiper or Seal = The wiper or seal of the unslotted guide pole is at or above the pole wiper.</p> <p>Seal Configuration = Mechanical shoe primary seal and a secondary seal.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP2TK4922	30 TAC Chapter 115, Storage of VOCs	R5112-6	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Welded tank using an external floating roof</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Primary Seal = Mechanical shoe</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized</p>	
OP2TK4922	40 CFR Part 60, Subpart Kb	60Kb-1	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
OP2TK4922	40 CFR Part 63, Subpart YY	63YY-1	<p>Source Type = Tank is located at an ethylene production facility and meets the size and vapor pressure requirements of Table 7 to be subject to § 63.1103.</p>	
EC4LTMISC1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-25	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
EC4LTMISC1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-25A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
EC4LTMISC1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-25B	<p>Chapter 115 Control Device Type = No control device.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Pressurized loading system.</p>	
EC4LTMISC1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-25C	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
EC4LTMISC1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-25D	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
EC4LTMISC1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-25E	<p>Chapter 115 Control Device Type = No control device.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Pressurized loading system.</p>	
EC4LTMISC2	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-26	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
EC4LTMISC2	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-26A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
EC4LTMISC2	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-26B	<p>Chapter 115 Control Device Type = No control device.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Pressurized loading system.</p>	
EC4LTMISC2	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-26C	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
EC4LTMISC2	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-26D	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
EC4LTMISC2	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-26E	<p>Chapter 115 Control Device Type = No control device.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Pressurized loading system.</p>	
ECULR1C4	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-2A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR1C4	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-2B	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR1C4	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-2C	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR1C4	40 CFR Part 63, Subpart G	63G-2	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>	
ECULR1CBD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-3A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR1CBD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-3B	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR1CBD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-3C	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR1CBD	40 CFR Part 63, Subpart G	63G-3	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>	
ECULR2C4	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-4A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR2C4	30 TAC Chapter 115, Loading	R5211-4B	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	and Unloading of VOC		<p>dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR2C4	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-4C	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR2C4	40 CFR Part 63, Subpart G	63G-4	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>	
ECULR2CBD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-5A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ECULR2CBD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-5B	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR2CBD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-5C	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR2CBD	40 CFR Part 63, Subpart G	63G-5	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>	
ECULR2MEOH	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-6	<p>Chapter 115 Control Device Type = Vapor control system with a chiller.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR2MEOH	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-7	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULR2MEOH	40 CFR Part 63, Subpart G	63G-6	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Condenser.</p> <p>Halogenated Emissions = There are no halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is operated and maintained under negative pressure.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p>	
ECULR2MEOH	40 CFR Part 63, Subpart G	63G-7	<p>Control Device = Flare.</p> <p>Halogenated Emissions = There are no halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p>	
ECULRACID	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULRACID	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1B	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULRACN	40 CFR Part 63, Subpart G	63G-9	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>	
ECULRVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-7A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULRVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-7B	<p>Chapter 115 Control Device Type = Vapor control system with a chiller.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULRVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-7C	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>	
ECULRVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-7D	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ECULRVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-7E	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTC4	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-8A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTC4	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-8B	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ECULTC4	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-8C	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTC4	40 CFR Part 63, Subpart G	63G-7	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>	
ECULTMEOH	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-9A	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>	
ECULTMEOH	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-9B	<p>Chapter 115 Control Device Type = Vapor control system with a chiller.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTMEOH	30 TAC Chapter 115, Loading and Unloading of	R5211-9C	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOC		<p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTMEOH	40 CFR Part 63, Subpart G	63G-8	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Condenser.</p> <p>Halogenated Emissions = There are no halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is operated and maintained under negative pressure.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p>	
ECULTMEOH	40 CFR Part 63, Subpart G	63G-8A	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Flare.</p> <p>Halogenated Emissions = There are no halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is operated and maintained under negative pressure.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ECULTNOHAP	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-10A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTNOHAP	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-10B	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>	
ECULTNOHAP	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-10C	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTNOHAP	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-10D	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-11A	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-11B	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>	
ECULTVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-11C	<p>Chapter 115 Control Device Type = Vapor control system with a chiller.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ECULTVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-11D	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
ECULTVOC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-11E	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
GRPLDBGDK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	<p>Chapter 115 Facility Type = Marine terminal</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>	
GRPLDBGDK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-2	<p>Chapter 115 Control Device Type = Vapor control system with a vapor combustor.</p> <p>Chapter 115 Facility Type = Marine terminal</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
GRPLDBGDK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-3	<p>Chapter 115 Facility Type = Marine terminal</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Marine Terminal Exemptions = The marine terminal is claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).</p> <p>Transfer Type = Only unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>VOC Flash Point = Flash point less than 150° F.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
GRPLDBGDK	40 CFR Part 61, Subpart BB	61BB-1	<p>Negative Applicability = The loading rack loads materials other than benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant.</p> <p>Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is greater than or equal to 70% benzene by weight.</p> <p>Annual Amount Loaded = Annual amount loaded is greater than or equal to 1.3 million liters (343,424 gallons).</p> <p>Loading Location = Marine loading only.</p> <p>Subpart BB Control Device Type = Incinerator other than a catalytic incinerator.</p> <p>Intermittent Control Device = The control device does not operate intermittently.</p> <p>Diverted Gas Stream = The vent gas stream cannot be diverted from the control device.</p>	
GRPLDBGDK	40 CFR Part 61, Subpart BB	61BB-2	<p>Negative Applicability = The loading rack loads materials other than benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant.</p> <p>Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is less than 70% benzene by weight.</p> <p>Annual Amount Loaded = Annual amount loaded is greater than or equal to 1.3 million liters (343,424 gallons).</p>	
GRPLDBGDK	40 CFR Part 63, Subpart Y	63Y-1	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is less than 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPLDBGDK	40 CFR Part 63, Subpart Y	63Y-2	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are subject to and complying with 40 CFR Part 61, Subpart BB.</p>	
GRPLDBGDK	40 CFR Part 63, Subpart Y	63Y-3	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Material Loaded = Material other than crude oil or gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Source Emissions = Source with emissions less than 10 and 25 tons.</p>	
GRPLOADBD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>	
GRPLOADBD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-2	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
GRPLOADBD	30 TAC Chapter 115, Loading	R5211-3	<p>Chapter 115 Control Device Type = Vapor control system with a flare.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	and Unloading of VOC		<p>dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
GRPLOADBD	40 CFR Part 63, Subpart G	63G-1A	<p>Control Device = Flare.</p> <p>Halogenated Emissions = There are no halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Closed Vent System = Closed vent system is operated and maintained under negative pressure.</p>	
GRPLOADBD	40 CFR Part 63, Subpart G	63G-1B	<p>Control Device = Flare.</p> <p>Halogenated Emissions = There are no halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Closed Vent System = Closed vent system is operated and maintained under negative pressure.</p>	
GRPLOADBD	40 CFR Part 63, Subpart G	63G-1C	<p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are routed to a fuel gas system or to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Closed Vent System = Closed vent system is operated and maintained under negative pressure.	
GRPLOADOP1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Loading and unloading. True Vapor Pressure = True vapor pressure less than 0.5 psia.	
GRPLOADPBD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Loading and unloading. True Vapor Pressure = True vapor pressure less than 0.5 psia.	
MSMLDMISC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-10	Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system. Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Loading and unloading. True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia. Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized. Control Options = Vapor balance system.	
OP2LOAD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Loading and unloading. True Vapor Pressure = True vapor pressure less than 0.5 psia.	
EC4HT1203	30 TAC Chapter 117, Subchapter B	R7ICI-17	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. Fuel Type #2 = Natural gas NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
EC4HT1203	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began after June 4, 2010. ANNUAL CAPACITY FACTOR = FEDERALLY ENFORCEABLE ANNUAL CAPACITY FACTOR OF 10% OR LESS	
EC4HT302	30 TAC Chapter 117, Subchapter B	R7300-2	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average RACT Date Placed in Service = On or before November 15, 1992 NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
EC4HT302	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
GRPLIQFURN	30 TAC Chapter 117, Subchapter B	R7ICI-4B	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Predictive emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
GRPOLFUR2	30 TAC Chapter 117, Subchapter B	R7301	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>NH3 Emission Limitation = Title 30 TAC § 117.310(c)(2)</p> <p>NOx Reduction = Post combustion control technique with ammonia injection</p> <p>Fuel Type #1 = Natural gas</p> <p>NH3 Monitoring = Mass balance</p> <p>Fuel Type #2 = Gaseous fuel other than natural gas, landfill gas or renewable non-fossil fuel gases</p> <p>NOx Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
GRPOLFURN	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Liquid</p> <p>NOx Monitoring System = Predictive emissions monitoring system</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
GRPOLSUHT	30 TAC Chapter 117, Subchapter B	R7ICI-2B	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 100 MMBtu/hr, but less than 200 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average RACT Date Placed in Service = On or before November 15, 1992 NOx Reduction = No NO _x control method Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases. NOx Monitoring System = Continuous emissions monitoring system Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
GRPOLSUHT	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
MEOHT7001	30 TAC Chapter 117, Subchapter B	R7301	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average NH3 Emission Limitation = Title 30 TAC § 117.310(c)(2) NOx Reduction = Post combustion control technique with ammonia injection Fuel Type #1 = Natural gas NH3 Monitoring = Mass balance Fuel Type #2 = Gaseous fuel other than natural gas, landfill gas or renewable non-fossil fuel gases NOx Monitoring System = Continuous emissions monitoring system Annual Heat Input = Annual heat input is greater than 2.2(10 ¹¹) Btu/yr, based on a rolling 12-month average. NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
MEOHT7001	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010. ANNUAL CAPACITY FACTOR = ANNUAL CAPACITY FACTOR OTHER THAN A FEDERALLY ENFORCEABLE ANNUAL CAPACITY FACTOR.	
MSMHT2801A	30 TAC Chapter 117, Subchapter B	R7300-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average RACT Date Placed in Service = On or before November 15, 1992 NOx Reduction = No NO _x control method Fuel Type #1 = Natural gas NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
MSMHT2801B	30 TAC Chapter 117, Subchapter B	R7300-1	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average RACT Date Placed in Service = On or before November 15, 1992 NOx Reduction = No NO _x control method Fuel Type #1 = Natural gas NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
MSMHT2801B	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
OFXHT4351	30 TAC Chapter 117, Subchapter B	R7ICI-3	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average RACT Date Placed in Service = On or before November 15, 1992 NOx Reduction = No NO _x control method Fuel Type #1 = Natural gas NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
OFXHT4351	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
OFXHT4360	30 TAC Chapter 117, Subchapter B	R7ICI-4	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average RACT Date Placed in Service = On or before November 15, 1992 NOx Reduction = No NO _x control method Fuel Type #1 = Natural gas NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
OFXHT4360	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
OFXHT4360C	30 TAC Chapter 117, Subchapter B	R7ICI-5	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average RACT Date Placed in Service = On or before November 15, 1992 NOx Reduction = No NO _x control method Fuel Type #1 = Natural gas NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
OFXHT4360C	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
OFXHT4361	30 TAC Chapter 117, Subchapter B	R7ICI-6	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average RACT Date Placed in Service = On or before November 15, 1992 NOx Reduction = No NO _x control method Fuel Type #1 = Natural gas NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000] NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)	
OFXHT4361	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
OP1HT3415	30 TAC Chapter 117, Subchapter B	R7ICI-8A	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent. Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a). Unit Type = Process heater CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr. CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS. NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average RACT Date Placed in Service = On or before November 15, 1992 NH3 Emission Limitation = Title 30 TAC § 117.310(c)(2) NOx Reduction = Post combustion control technique with ammonia injection	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NH3 Monitoring = Mass balance</p> <p>NOx Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
OP1HT3415	30 TAC Chapter 117, Subchapter B	R7ICI-8B	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Predictive emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
OP1HT3415	30 TAC Chapter 117, Subchapter B	R7ICI-8C	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 200 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Continuous emissions monitoring system</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on a rolling 12-month average.</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
OP1HT3601	30 TAC Chapter	R7ICI-4	Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	117, Subchapter B		<p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
OP1HT3601	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
OP1HT3701	30 TAC Chapter 117, Subchapter B	R7ICI-3	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p> <p>Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
OP1HT3701	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
OP2HT4601	30 TAC Chapter 117, Subchapter B	R7ICI-7	<p>Diluent CEMS = The process heater does not use a carbon dioxide CEMS to monitor diluent.</p> <p>Fuel Flow Monitoring = Fuel flow is monitored with a totalizing fuel flow meter per 30 TAC §§ 117.140(a), 117.340(a) or 117.440(a).</p> <p>Unit Type = Process heater</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Maximum Rated Capacity = Maximum rated capacity is at least 2 MMBtu/hr, but less than 40 MMBtu/hr.</p> <p>CO Monitoring System = Emissions are monitored using methods other than CEMS or PEMS.</p> <p>NOx Emission Limit Basis = Emission limit basis is not a 30 day rolling average or a block one-hour average</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>NOx Reduction = No NO_x control method</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas, landfill gas, or renewable non-fossil fuel gases.</p> <p>NOx Monitoring System = Maximum emission rate testing [in accordance with 30 TAC § 117.8000]</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(8)</p>	
OP2HT4601	40 CFR Part 63, Subpart DDDDD	63DDDDD-1	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
GRPBOILER	30 TAC Chapter 117, Subchapter B	R7ICI-1A	<p>NOx Emission Limitation = Title 30 TAC § 117.310(d)(3) [relating to mass emissions cap and trade in 30 TAC Chapter 101, Subchapter H, Division 3 and Emission Specifications for Attainment Demonstration].</p> <p>Unit Type = Other industrial, commercial, or institutional boiler.</p> <p>Maximum Rated Capacity = MRC is greater than or equal to 250 MMBtu/hr.</p> <p>NOx Monitoring System = Continuous emissions monitoring system.</p> <p>Fuel Flow Monitoring = Unit operates with a NO_x and diluent CEMS and monitors stack exhaust flow per 30 TAC §§ 117.140(a)(2)(A), 117.340(a)(2)(A) or 117.440(a)(2)(A).</p> <p>RACT Date Placed in Service = On or before November 15, 1992.</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option.</p> <p>CO Monitoring System = Continuous emissions monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>EGF System Cap Unit = The unit is not used as an electric generating facility to generate electricity for sale to the electric grid.</p> <p>Fuel Type #1 = Gaseous fuel other than natural gas landfill gas or renewable non-fossil fuel gases.</p> <p>NH3 Emission Limitation = Title 30 TAC § 117.310(c)(2).</p> <p>NOx Emission Limit Average = Emission limit in pounds/hour on a block one-hour average.</p> <p>NOx Reductions = No NO_x reduction.</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on rolling 12-month average.</p>	
GRPBOILER	30 TAC Chapter 117, Subchapter B	R7ICI-1B	<p>NOx Emission Limitation = Title 30 TAC § 117.310(d)(3) [relating to mass emissions cap and trade in 30 TAC Chapter 101, Subchapter H, Division 3 and Emission Specifications for Attainment Demonstration].</p> <p>Unit Type = Other industrial, commercial, or institutional boiler.</p> <p>Maximum Rated Capacity = MRC is greater than or equal to 250 MMBtu/hr.</p> <p>NOx Monitoring System = Continuous emissions monitoring system.</p> <p>Fuel Flow Monitoring = Unit operates with a NO_x and diluent CEMS and monitors stack exhaust flow per 30 TAC §§ 117.140(a)(2)(A), 117.340(a)(2)(A) or 117.440(a)(2)(A).</p> <p>RACT Date Placed in Service = On or before November 15, 1992.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 400 ppmv option.</p> <p>CO Monitoring System = Continuous emissions monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>EGF System Cap Unit = The unit is not used as an electric generating facility to generate electricity for sale to the electric grid.</p> <p>Fuel Type #1 = Liquid fuel</p> <p>NH3 Emission Limitation = Title 30 TAC § 117.310(c)(2).</p> <p>NOx Emission Limit Average = Emission limit in pounds/hour on a block one-hour average.</p> <p>NOx Reductions = No NO_x reduction.</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10¹¹) Btu/yr, based on rolling 12-month average.</p>	
GRPBOILER	40 CFR Part 60, Subpart D	60D-1A	<p>Construction/Modification Date = After August 17, 1971, and on or before December 22, 1976.</p> <p>D-Series Fuel Type #1 = Gaseous fossil fuel.</p> <p>Covered Under Subpart Da = The steam generating unit is not covered under 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing fossil fuel-fired steam generating unit.</p> <p>Alternate 43D = No alternative requirement is used for SO₂, unit is complying with requirements of § 60.43(a) and (b).</p> <p>Heat Input Rate = Heat input rate is greater than 250 MMBtu/hr (73 MW).</p> <p>Alternate 42C = The facility is meeting the requirements of § 60.42(a) for PM.</p> <p>Alternate 44E = The facility is meeting the requirements of § 60.44(a), (b), and (d) for NO_x.</p> <p>Flue Gas Desulfurization = The unit does not utilize a flue gas desulfurization device.</p> <p>PM CEMS = The facility does not use a CEMS to measure PM.</p> <p>Fuel Sampling and Analysis = The unit does not use fuel sampling and analysis for monitoring of sulfur dioxide emissions.</p> <p>Gas or Liquid Fuel Only = Burns only gaseous or liquid fossil fuel (not residual oil) with potential SO₂ emissions rates of 0.060 lb/MMBtu or less, does not use post combustion technology to reduce of SO₂ or PM, and monitors SO₂ emissions by sampling or fuel receipts.</p> <p>Cyclone-Fired Unit = The unit is not a cyclone-fired unit.</p> <p>Fuels with 0.33 Percent or Less Sulfur = Facility does not use post combustion technology (except a wet scrubber) for reducing PM, SO₂, or CO, burns only gaseous fuels or fuel oils that contain 0.30 % sulfur by weight or less, and operates so CO emissions are 0.15 lb/MMBtu average.</p> <p>NOx Monitoring Type = It was not demonstrated during the performance test that emissions of NO_x are less than 70% of applicable standards in 40 CFR § 60.44.</p> <p>PM CEMS Petition = No petition has been granted to install a PM CEMS as an alternative to the CEMS for monitoring opacity emissions.</p>	
EMERFLARE	30 TAC Chapter 111, Visible Emissions	R1111-2	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p>	
EMERFLARE	30 TAC Chapter 111, Visible	R1111-3	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used only under emergency or upset conditions.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Emissions			
EMERFLARE	40 CFR Part 60, Subpart A	60A-1A	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
EMERFLARE	40 CFR Part 60, Subpart A	60A-1B	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)</p>	
EMERFLARE	40 CFR Part 60, Subpart A	60A-1C	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).</p>	
EMERFLARE	40 CFR Part 63, Subpart A	63A-1A	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
EMERFLARE	40 CFR Part 63, Subpart A	63A-1B	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).</p>	
EMERFLARE	40 CFR Part 63, Subpart A	63A-1C	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).	
EUTFL1701	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.	
EUTFL1701	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d). Out of Service = Flare was not permanently out of service by April 1, 2006. Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time. Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time. Multi-Purpose Usage = Flare is used for abatement of emissions from marine loading or transport vessel loading and unloading operations AND for abatement of emissions from scheduled or unscheduled maintenance, startup or shutdown activities AND as an emergency flare. Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1). Alternative Monitoring = No alternative monitoring and test methods are used. Physical Seal = Flare is equipped with a flow monitor or indicator. Minor Modification = No minor modifications to the monitoring and test methods are used. Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC. Flare Type = Flare is in multi-purpose service.	
EUTFL1701	40 CFR Part 60, Subpart A	60A-1A	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
EUTFL1701	40 CFR Part 60, Subpart A	60A-1B	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)	
EUTFL1701	40 CFR Part 60, Subpart A	60A-1C	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EUTFL1701	40 CFR Part 63, Subpart A	63A-1A	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
EUTFL1701	40 CFR Part 63, Subpart A	63A-1B	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).</p>	
EUTFL1701	40 CFR Part 63, Subpart A	63A-1C	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).</p>	
MEOHFLARE	30 TAC Chapter 111, Visible Emissions	R1111-2	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p>	
MIPFL2501	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p>	
MIPFL2501	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d).</p> <p>Out of Service = Flare was not permanently out of service by April 1, 2006.</p> <p>Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time.</p> <p>Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time.</p> <p>Multi-Purpose Usage = Flare is used for abatement of emissions from scheduled or unscheduled maintenance, startup or shutdown activities AND as an emergency flare.</p> <p>Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1).</p> <p>Alternative Monitoring = No alternative monitoring and test methods are used.</p> <p>Physical Seal = Flare is equipped with a flow monitor or indicator.</p> <p>Minor Modification = No minor modifications to the monitoring and test methods are used.</p> <p>Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC.</p> <p>Flare Type = Flare is in multi-purpose service.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
MIPFL2501	40 CFR Part 63, Subpart A	63A-1A	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
MIPFL2501	40 CFR Part 63, Subpart A	63A-1B	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).	
MIPFL2501	40 CFR Part 63, Subpart A	63A-1C	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).	
MPBFL2502	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.	
MPBFL2502	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d). Out of Service = Flare was not permanently out of service by April 1, 2006. Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time. Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time. Multi-Purpose Usage = Flare is used for abatement of emissions from scheduled or unscheduled maintenance, startup or shutdown activities AND as an emergency flare. Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1). Alternative Monitoring = No alternative monitoring and test methods are used. Physical Seal = Flare is equipped with a flow monitor or indicator. Minor Modification = No minor modifications to the monitoring and test methods are used. Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC. Flare Type = Flare is in multi-purpose service.	
MPBFL2502	40 CFR Part 63,	63A-1A	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart A		Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
MPBFL2502	40 CFR Part 63, Subpart A	63A-1B	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).	
MPBFL2502	40 CFR Part 63, Subpart A	63A-1C	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).	
OLH2FLARE	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.	
OP1FL3801	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.	
OP1FL3801	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d). Out of Service = Flare was not permanently out of service by April 1, 2006. Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time. Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time. Multi-Purpose Usage = Flare is used for abatement of emissions from scheduled or unscheduled maintenance, startup or shutdown activities AND as an emergency flare. Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1). Alternative Monitoring = No alternative monitoring and test methods are used. Physical Seal = Flare is equipped with a flow monitor or indicator. Minor Modification = No minor modifications to the monitoring and test methods are used. Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC. Flare Type = Flare is in multi-purpose service.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP1FL3801	40 CFR Part 60, Subpart A	60A-1A	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
OP1FL3801	40 CFR Part 60, Subpart A	60A-1B	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)</p>	
OP1FL3801	40 CFR Part 60, Subpart A	60A-1C	<p>Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18.</p> <p>Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4).</p> <p>Flare Assist Type = Steam-assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).</p>	
OP1FL3801	40 CFR Part 63, Subpart A	63A-1A	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)</p>	
OP1FL3801	40 CFR Part 63, Subpart A	63A-1B	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).</p>	
OP1FL3801	40 CFR Part 63, Subpart A	63A-1C	<p>Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63.</p> <p>Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8).</p> <p>Flare Assist Type = Steam assisted</p> <p>Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec).</p> <p>Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP2FL4801	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.	
OP2FL4801	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d). Out of Service = Flare was not permanently out of service by April 1, 2006. Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time. Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time. Multi-Purpose Usage = Flare is used for abatement of emissions from scheduled or unscheduled maintenance, startup or shutdown activities AND as an emergency flare. Flow Rate = Flow rate of the gas routed to the flare is determined using the requirements of § 115.725(d)(1). Alternative Monitoring = No alternative monitoring and test methods are used. Physical Seal = Flare is equipped with a flow monitor or indicator. Minor Modification = No minor modifications to the monitoring and test methods are used. Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC. Flare Type = Flare is in multi-purpose service.	
OP2FL4801	40 CFR Part 60, Subpart A	60A-1A	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
OP2FL4801	40 CFR Part 60, Subpart A	60A-1B	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)	
OP2FL4801	40 CFR Part 60, Subpart A	60A-1C	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).	
OP2FL4801	40 CFR Part 63, Subpart A	63A-1A	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
OP2FL4801	40 CFR Part 63, Subpart A	63A-1B	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).	
OP2FL4801	40 CFR Part 63, Subpart A	63A-1C	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).	
FUGITIVES	30 TAC Chapter 115, HRVOC Fugitive Emissions	R5780-ALL	SOP Index No. = Owner/Operator assumes HRVOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter H, Division 3 with no alternate control or control device. Alternative Work Practice in § 115.358 = No components are complying with the alternative work practice requirements in 30 TAC § 115.358. Title 30 TAC §115.780 Applicable = The fugitive unit contains a defined process and Highly Reactive VOC. Less Than 250 Components at Site = The fugitive unit is located at a site with at least 250 fugitive components in VOC service. Weight Percent HRVOC = Components in the fugitive unit contact process fluids that contain less than 5.0% HRVOC by weight and process fluids that contain HRVOC at 5.0%, or greater, by weight on an annual average basis.	
FUGITIVES	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.	
FUGITIVES	40 CFR Part 60, Subpart VV	60VVALL	SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in VOC service subject to 40 CFR Part 60, Subpart VV with no alternate control or control devices. Flare = The fugitive unit contains flares. Equivalent Emission Limitation = No equivalent emission limitation is used for flares. Complying with 40 CFR § 60.482-10 = Flares are complying with § 60.482-10.	
FUGITIVES	40 CFR Part 61, Subpart J	61J-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS IN BENZENE SERVICE SUBJECT TO NESHAPS J WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>40 CFR 61 (NESHAP) SUBPART J DESIGN CAPACITY = SITE IS DESIGNED TO PRODUCE OR USE MORE THAN 1,000 MEGAGRAMS OF BENZENE PER YEAR</p> <p>ANY COMPONENT IN BENZENE SERVICE [NESHAP J] = THE FACILITY CONTAINS ANY COMPONENT(S) IN BENZENE SERVICE</p> <p>40 CFR 61 (NESHAP) SUBPART J ALTERNATE MEANS OF EMISSION LIMITATION (AMEL) = NOT USING ALTERNATE MEANS OF EMISSION LIMITATION.</p>	
FUGITIVES	40 CFR Part 61, Subpart V	61V-ALL	<p>SOP Index No. = Owner or operator assumes fugitive unit control requirements for all components in benzene service subject to 40 CFR Part 61, Subpart V with no alternate control or control device.</p> <p>Closed-vent Systems = No alternate method of emission limitation is used for closed vent systems or other control devices.</p> <p>Enclosed Combustion Device = The fugitive unit does not contain enclosed combustion devices in VHAP service.</p> <p>Flare = The fugitive unit does not contain flares.</p> <p>Vapor Recovery System = The fugitive unit does not contain vapor recovery systems in VHAP service.</p> <p>AMEL = No alternate method of emission limitation is used for compressors.</p> <p>Complying with 40 CFR § 61.242-11(f)(1) = Closed vent systems are complying with § 61.242-11(f)(1).</p> <p>AMEL = No alternate method of emission limitation is used for pumps.</p> <p>Complying with 40 CFR § 61.242-3 = Compressors are complying with § 61.242-3.</p> <p>Complying with 40 CFR § 61.242-4 = Pressure relief devices in gas/vapor service are complying with § 61.242-4.</p> <p>Complying with 40 CFR § 61.242-5 = Sampling connection systems are complying with § 61.242-5.</p> <p>Complying with 40 CFR § 61.242-7 = Valves are complying with § 61.242-7.</p> <p>Complying with 40 CFR § 61.242-9 = Product accumulator vessels are complying with § 61.242-9.</p> <p>AMEL = No alternate method of emission limitation is used for pressure relief devices in liquid service.</p> <p>Complying with 40 CFR § 61.242-2 = Pumps are complying with 40 CFR § 61.242-2.</p> <p>Complying with 40 CFR § 61.242-6 = Open-ended valves or lines are complying with § 61.242-6.</p> <p>Complying with 40 CFR § 61.242-8 = Pressure relief devices in liquid service are complying with § 61.242-8.</p>	
FUGITIVES	40 CFR Part 63, Subpart FFFF	63FFFF-1	Existing Source = Fugitive unit contains equipment in an existing Miscellaneous Chemical Processing Unit.	
FUGITIVES	40 CFR Part 63, Subpart H	63HALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.	
FUGITIVES	40 CFR Part 63, Subpart H	63HALL-VNT	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>BYPASS LINES = FUGITIVE UNIT WITH A CLOSED-VENT SYSTEM DOES NOT CONTAIN A BY-PASS LINE THAT COULD DIVERT A VENT STREAM AWAY FROM THE CONTROL DEVICE AND TO THE ATMOSPHERE</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT UNSAFE TO INSPECT = FOR A FUGITIVE UNIT THAT CONTAINS ANY CLOSED-VENT SYSTEM, THERE ARE NO PARTS DESIGNATED AS UNSAFE TO INSPECT DIFFICULT TO INSPECT = FOR A FUGITIVE UNIT THAT CONTAINS ANY CLOSED-VENT SYSTEM, THERE ARE NO PARTS DESIGNATED AS DIFFICULT TO INSPECT VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR FLARES (CLOSED VENT SYSTEMS) = COMPONENT PRESENT	
ECUCT1701A	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-7	Cooling Tower Heat Exchange System Exemptions = Each individual heat exchanger of the cooling tower heat exchange system does not have greater than 100 ppmw HRVOCs in the process side fluid.	
ECUCT1701B	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-8	Cooling Tower Heat Exchange System Exemptions = Each individual heat exchanger of the cooling tower heat exchange system does not have greater than 100 ppmw HRVOCs in the process side fluid.	
ECUCT604	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-1	Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption. Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor. Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764. Design Capacity = Design capacity to circulate 8000 gpm or greater. Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a). Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764. Flow Monitoring/Testing Method = Choosing to use a continuous flow monitor on each inlet of each cooling tower in accordance with § 115.764(a)(1), (b)(1), or (h)(1). Total Strippable VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a). On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.	
MBTCT2402	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-4	Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system in which each individual heat exchanger with greater than 100 ppmw HRVOCs is operated with the minimum pressure on the cooling water side at least 5 psig greater than the maximum pressure on the process side.	
MIPCT2401	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-5	Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system in which each individual heat exchanger with greater than 100 ppmw HRVOCs is operated with the minimum pressure on the cooling water side at least 5 psig greater than the maximum pressure on the process side.	
OP1CT3811	30 TAC Chapter	R5760-2	Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, HRVOC Cooling Towers		<p>exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764.</p> <p>Flow Monitoring/Testing Method = Choosing to use the maximum potential flow rate based on the manufacturer's pump performance data in accordance with §115.764(e)(1).</p> <p>Total Strippable VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.</p>	
OP2CT4811	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-3	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764.</p> <p>Flow Monitoring/Testing Method = Choosing to use the maximum potential flow rate based on the manufacturer's pump performance data in accordance with §115.764(e)(1).</p> <p>Total Strippable VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.</p>	
ECUSUEAPI	30 TAC Chapter 115, Water Separation	R5131-2	<p>Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910.</p> <p>Exemption = Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure less than 0.5 psia (3.4 kPa) obtained from any equipment.</p>	
ECUSUWAPI	30 TAC Chapter 115, Water Separation	R5131-1	<p>Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910.</p> <p>Exemption = Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure less than 0.5 psia (3.4 kPa) obtained from any equipment.</p>	
EUTDM0701	40 CFR Part 61, Subpart FF	61FF-19A	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
EUTDM0701	40 CFR Part 61, Subpart FF	61FF-19B	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
EUTDM0701	40 CFR Part 63, Subpart G	63G-29A	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>	
EUTDM0701	40 CFR Part 63, Subpart G	63G-29B	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>	
EUTDM0801	40 CFR Part 61, Subpart FF	61FF-19A	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
EUTDM0801	40 CFR Part 61, Subpart FF	61FF-19B	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
EUTDM0801	40 CFR Part 63, Subpart G	63G-29A	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>	
EUTDM0801	40 CFR Part 63, Subpart G	63G-29B	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>	
EUTDM8801	40 CFR Part 61, Subpart FF	61FF-19A	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
EUTDM8801	40 CFR Part 61, Subpart FF	61FF-19B	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EUTDM8801	40 CFR Part 63, Subpart G	63G-29A	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>	
EUTDM8801	40 CFR Part 63, Subpart G	63G-29B	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>	
EUTDM8804	40 CFR Part 61, Subpart FF	61FF-19A	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
EUTDM8804	40 CFR Part 61, Subpart FF	61FF-19B	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
EUTDM8804	40 CFR Part 63, Subpart G	63G-29A	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>	
EUTDM8804	40 CFR Part 63, Subpart G	63G-29B	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>	
MBTWWCPI	30 TAC Chapter 115, Water Separation	R5131-1	<p>Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910.</p> <p>Exemption = Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure less than 0.5 psia (3.4 kPa) obtained from any equipment.</p>	
MEOSP3101	30 TAC Chapter 115, Water Separation	R5131-1	<p>Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910.</p> <p>Exemption = Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure less than 0.5 psia (3.4 kPa) obtained from any equipment.</p>	
MPBDAPI	30 TAC Chapter 115, Water Separation	R5131-1	<p>Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910.</p> <p>Exemption = Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure less than 0.5 psia (3.4 kPa) obtained from any equipment.</p>	
OP1DM3453	40 CFR Part 61, Subpart FF	61FF-1	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
OP1SU38094	40 CFR Part 61, Subpart FF	61FF-5	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = CARBON ADSORPTION SYSTEM NOT REGENERATING BED DIRECTLY IN DEVICE</p> <p>Engineering Calculations = PERFORMANCE TEST IS BEING USED TO DETERMINE COMPLIANCE OF A CONTROL DEVICE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Carbon Replacement Interval = EXHAUST IS MONITORED ON A REGULAR SCHEDULE AND CARBON IS REPLACED IMMEDIATELY UPON BREAKTHROUGH</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
OP1SU38094	40 CFR Part 61, Subpart FF	61FF-6	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS A BY-PASS LINE THAT COULD DIVERT THE STREAM AWAY FROM THE CONTROL DEVICE</p> <p>By-Pass Line Valve = A FLOW INDICATOR IS INSTALLED AT THE ENTRANCE TO THE BY-PASS LINE.</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = BOILER OR PROCESS HEATER, DESIGN HEAT INPUT ≥ 44 MW, REDUCING ORGANICS BY 95 WEIGHT PERCENT OR GREATER</p> <p>Engineering Calculations = ENGINEERING CALCULATIONS ARE USED TO DEMONSTRATE CONTROL DEVICE PERFORMANCE</p> <p>Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
OP1SU38094	40 CFR Part 61, Subpart FF	61FF-7	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS A BY-PASS LINE THAT COULD DIVERT THE STREAM AWAY FROM THE CONTROL DEVICE</p> <p>By-Pass Line Valve = A FLOW INDICATOR IS INSTALLED AT THE ENTRANCE TO THE BY-PASS LINE.</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = BOILER OR PROCESS HEATER, DESIGN HEAT INPUT ≥ 44 MW, ACHIEVING TOC CONCENTRATION OF 20 PPMV</p> <p>Engineering Calculations = ENGINEERING CALCULATIONS ARE USED TO DEMONSTRATE CONTROL DEVICE PERFORMANCE</p> <p>Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
OP1SU38094	40 CFR Part 61, Subpart FF	61FF-8	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS A BY-PASS LINE THAT COULD DIVERT THE STREAM AWAY FROM THE CONTROL DEVICE</p> <p>By-Pass Line Valve = A FLOW INDICATOR IS INSTALLED AT THE ENTRANCE TO THE BY-PASS LINE.</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = BOILER OR PROCESS HEATER, DESIGN HEAT INPUT ≥ 44 MW, REDUCING</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>ORGANICS BY 95 WEIGHT PERCENT OR GREATER</p> <p>Engineering Calculations = PERFORMANCE TEST IS BEING USED TO DETERMINE COMPLIANCE OF A CONTROL DEVICE</p> <p>Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
OP1SU38094	40 CFR Part 61, Subpart FF	61FF-9	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS A BY-PASS LINE THAT COULD DIVERT THE STREAM AWAY FROM THE CONTROL DEVICE</p> <p>By-Pass Line Valve = A FLOW INDICATOR IS INSTALLED AT THE ENTRANCE TO THE BY-PASS LINE.</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = BOILER OR PROCESS HEATER, DESIGN HEAT INPUT ≥ 44 MW, ACHIEVING TOC CONCENTRATION OF 20 PPMV</p> <p>Engineering Calculations = PERFORMANCE TEST IS BEING USED TO DETERMINE COMPLIANCE OF A CONTROL DEVICE</p> <p>Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
OP1SU38094	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>Process Wastewater = Oil-Water Separator receives, manages or treats process wastewater as defined in 40 CFR Part 63, Subpart FFFF</p> <p>Alt 63G Mon Parameters = The EPA Administrator has not approved an alternate monitoring parameter or no alternate has been requested.</p> <p>Bypass Lines = Bypass lines are monitored by flow indicators.</p> <p>Combination Of Control Devices = The vent stream is treated using a single control device.</p> <p>Unit Category = Oil/water separator complies with 40 CFR § 63.137(a).</p> <p>Control Devices = Boiler or process heater with a design heat input capacity greater than or equal to 44 MW.</p> <p>Control Requirement = Fixed roof and a closed vent system that routes the organic hazardous air pollutant vapors vented from the oil-water separator to a control device.</p> <p>Floating Roof Alternate Monitoring Parameters = The EPA Administrator has not approved an alternate monitoring parameter for the floating roof or no alternate has been requested.</p> <p>Halogenated = The stream is determined as non-halogenated.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP1SU38094	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = BYPASS LINES ARE MONITORED BY FLOW INDICATORS</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = BOILER OR PROCESS HEATER WITH A DESIGN HEAT INPUT CAPACITY GREATER THAN OR EQUAL TO 44 MW</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p> <p>Continuous Monitoring = COMPLYING WITH THE CONTINUOUS MONITORING REQUIREMENTS OF § 63.143(E)(1) OR § 63.143(E)(2) IN TABLE 13</p>	
OP1SU38094	40 CFR Part 63, Subpart G	63G-14	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = BYPASS LINES ARE MONITORED BY FLOW INDICATORS</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = BOILER OR PROCESS HEATER WITH A DESIGN HEAT INPUT CAPACITY GREATER THAN OR EQUAL TO 44 MW</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p> <p>Continuous Monitoring = COMPLYING WITH THE CONTINUOUS MONITORING REQUIREMENTS OF § 63.143(E)(1) OR § 63.143(E)(2) IN TABLE 13</p>	
OP2DM4453	40 CFR Part 61,	61FF-1	Alternate Means of Compliance = NO	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart FF		<p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = FLARE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
OP2SU48094	30 TAC Chapter 115, Water Separation	R5131-9	<p>Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910.</p> <p>Exemption = Water separator does not qualify for exemption.</p> <p>Emission Control Option = Vapor recovery system which satisfies the provisions of 30 TAC § 115.131.</p> <p>Control Device = Control device or vapor recovery system other than a chiller, carbon adsorber, or incinerator.</p>	
OP2SU48094	40 CFR Part 61, Subpart FF	61FF-5	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = CARBON ADSORPTION SYSTEM NOT REGENERATING BED DIRECTLY IN DEVICE</p> <p>Engineering Calculations = PERFORMANCE TEST IS BEING USED TO DETERMINE COMPLIANCE OF A CONTROL DEVICE</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Carbon Replacement Interval = EXHAUST IS MONITORED ON A REGULAR SCHEDULE AND CARBON IS REPLACED IMMEDIATELY UPON BREAKTHROUGH</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
OP2SU48094	40 CFR Part 61, Subpart FF	61FF-6	<p>Alternate Means of Compliance = NO</p> <p>By-Pass Line = THE CLOSED VENT SYSTEM HAS A BY-PASS LINE THAT COULD DIVERT THE STREAM AWAY FROM THE CONTROL DEVICE</p> <p>By-Pass Line Valve = A FLOW INDICATOR IS INSTALLED AT THE ENTRANCE TO THE BY-PASS LINE.</p> <p>Alternative Standards for Oil-Water Separator = NO</p> <p>Control Device Type/Operation = BOILER OR PROCESS HEATER, DESIGN HEAT INPUT ≥ 44 MW, REDUCING ORGANICS BY 95 WEIGHT PERCENT OR GREATER</p> <p>Engineering Calculations = ENGINEERING CALCULATIONS ARE USED TO DEMONSTRATE CONTROL DEVICE PERFORMANCE</p> <p>Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC) Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349	
OP2SU48094	40 CFR Part 61, Subpart FF	61FF-7	Alternate Means of Compliance = NO By-Pass Line = THE CLOSED VENT SYSTEM HAS A BY-PASS LINE THAT COULD DIVERT THE STREAM AWAY FROM THE CONTROL DEVICE By-Pass Line Valve = A FLOW INDICATOR IS INSTALLED AT THE ENTRANCE TO THE BY-PASS LINE. Alternative Standards for Oil-Water Separator = NO Control Device Type/Operation = BOILER OR PROCESS HEATER, DESIGN HEAT INPUT ≥ 44 MW, ACHIEVING TOC CONCENTRATION OF 20 PPMV Engineering Calculations = ENGINEERING CALCULATIONS ARE USED TO DEMONSTRATE CONTROL DEVICE PERFORMANCE Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC) Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349	
OP2SU48094	40 CFR Part 61, Subpart FF	61FF-8	Alternate Means of Compliance = NO By-Pass Line = THE CLOSED VENT SYSTEM HAS A BY-PASS LINE THAT COULD DIVERT THE STREAM AWAY FROM THE CONTROL DEVICE By-Pass Line Valve = A FLOW INDICATOR IS INSTALLED AT THE ENTRANCE TO THE BY-PASS LINE. Alternative Standards for Oil-Water Separator = NO Control Device Type/Operation = BOILER OR PROCESS HEATER, DESIGN HEAT INPUT ≥ 44 MW, REDUCING ORGANICS BY 95 WEIGHT PERCENT OR GREATER Engineering Calculations = PERFORMANCE TEST IS BEING USED TO DETERMINE COMPLIANCE OF A CONTROL DEVICE Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC) Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349	
OP2SU48094	40 CFR Part 61, Subpart FF	61FF-9	Alternate Means of Compliance = NO By-Pass Line = THE CLOSED VENT SYSTEM HAS A BY-PASS LINE THAT COULD DIVERT THE STREAM AWAY FROM THE CONTROL DEVICE By-Pass Line Valve = A FLOW INDICATOR IS INSTALLED AT THE ENTRANCE TO THE BY-PASS LINE. Alternative Standards for Oil-Water Separator = NO Control Device Type/Operation = BOILER OR PROCESS HEATER, DESIGN HEAT INPUT ≥ 44 MW, ACHIEVING TOC CONCENTRATION OF 20 PPMV	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Engineering Calculations = PERFORMANCE TEST IS BEING USED TO DETERMINE COMPLIANCE OF A CONTROL DEVICE</p> <p>Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF</p> <p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE</p> <p>Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC)</p> <p>Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349</p>	
OP2SU48094	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = BYPASS LINES ARE MONITORED BY FLOW INDICATORS</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = BOILER OR PROCESS HEATER WITH A DESIGN HEAT INPUT CAPACITY GREATER THAN OR EQUAL TO 44 MW</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p> <p>Continuous Monitoring = COMPLYING WITH THE CONTINUOUS MONITORING REQUIREMENTS OF § 63.143(E)(1) OR § 63.143(E)(2) IN TABLE 13</p>	
OP2SU48094	40 CFR Part 63, Subpart G	63G-14	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.172</p> <p>New Source = FACILITY IS An EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = BYPASS LINES ARE MONITORED BY FLOW INDICATORS</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = BOILER OR PROCESS HEATER WITH A DESIGN HEAT INPUT CAPACITY GREATER THAN</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>OR EQUAL TO 44 MW</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p> <p>Continuous Monitoring = COMPLYING WITH THE CONTINUOUS MONITORING REQUIREMENTS OF § 63.143(E)(1) OR § 63.143(E)(2) IN TABLE 13</p>	
EALSP4066	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
EALSP4066	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
EC4HT1202	30 TAC Chapter 111, Visible Emissions	R1111-6	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
EC4RX1208	30 TAC Chapter 115, HRVOC Vent Gas	R5720-2	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
EC4RX1208	30 TAC Chapter 115, HRVOC Vent Gas	R5720-4	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft3/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a control device other than a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
EC4RX1208	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
EC4RX1208	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
EC4RX1208	30 TAC Chapter 115, Vent Gas Controls	R5121-4	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
EC4TO	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
EC5SP334	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
EC5SP334	30 TAC Chapter 115, Vent Gas Controls	R5122-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
EC5SP349	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
EC5SP349	30 TAC Chapter 115, Vent Gas Controls	R5122-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
EUTFL1701V	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Testing Requirements = Continuous emissions monitoring system in lieu of testing requirements in § 115.725(a).</p>	
EUTFL1701V	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
EUTFL1701V	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
EUTFL1701V	40 CFR Part 63, Subpart FFFF	63FFFF-2	<p>Designated Grp1 = The emission stream is designated as Group 1.</p> <p>Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control.</p> <p>Designated Hal = The emission stream is not designated as halogenated.</p> <p>Determined Hal = The emission stream is determined to be non-halogenated.</p> <p>Prior Eval = The data from a prior evaluation or assessment is not used.</p> <p>Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or a waiver has not been requested.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p>	
EUTFL1701V	40 CFR Part 63, Subpart G	63G-1	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>	
GRPZVENT	30 TAC Chapter 115, HRVOC Vent Gas	R5720-5	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Max Flow Rate = The vent gas stream has a maximum potential flow rate less than or equal to 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Exempt Date = The vent gas stream is not exempt.</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Testing Requirements = Process knowledge to determine maximum potential HRVOC hourly emissions for analyzer vents, stream system vents, vent gas streams with no HRVOC except during emission event or degassing safety device in lieu of testing.</p>	
GRPALZVENT	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
GRPC4VENT1	30 TAC Chapter 115, HRVOC Vent Gas	R5720-2	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
GRPC4VENT1	30 TAC Chapter 115, HRVOC Vent Gas	R5720-4	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a control device other than a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
GRPC4VENT1	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
GRPC4VENT1	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor combustor not considered to be a flare.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
GRPC4VENT1	30 TAC Chapter 115, Vent Gas Controls	R5121-4	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
GRPLIQFURN	30 TAC Chapter 111, Visible Emissions	R1111-5	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPMTVENT1	30 TAC Chapter 115, HRVOC Vent Gas	R5720-4	<p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft3/hr).</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a flare.</p>	
GRPMTVENT1	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
GRPOL1FURV	30 TAC Chapter 115, HRVOC Vent Gas	R5720-6	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft3/hr).</p> <p>Exempt Date = The vent gas stream is not exempt.</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a control device other than a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
GRPOL1FURV	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
GRPOL1FURV	30 TAC Chapter 115, Vent Gas Controls	R5121-28	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
GRPOL1FURV	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
GRPOL2FURV	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRPOL2FURV	30 TAC Chapter 115, Vent Gas Controls	R5121-28	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
GRPOL2FURV	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
GRPOLFUR2	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
GRPOLFUR2V	30 TAC Chapter 111, Visible Emissions	R1111	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
GRPOLFUR2V	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Acetal resins production	
GRPOLFURN	30 TAC Chapter 111, Visible Emissions	R1111-3	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
GRPOLFURN	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
GRPOLSEALV	30 TAC Chapter 115, Vent Gas	R5121-1	Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Controls		<p>115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
GRPOLSUHT	30 TAC Chapter 111, Visible Emissions	R1111-4	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
GRPOLSUHTV	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a control device other than a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
GRPOLSUHTV	30 TAC Chapter 115, Vent Gas Controls	R5121-29	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			specifically classified under the rule.	
GRPOLSUHTV	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
GRPSMAPMV	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
GRPSMAPMV	30 TAC Chapter 115, Vent Gas Controls	R5121-4	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.	
MBTSP4010	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
MBTSP4010	40 CFR Part 63, Subpart G	63G-1	<p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Regulation = Owners or operator is required to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>Flow Rate = Flow rate is less than 0.005 scm/min.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p>	
MEOHANLZ	30 TAC Chapter 115, Vent Gas Controls	R5121-1B	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
MEOHT7001V	30 TAC Chapter 111, Visible Emissions	R1111	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
MEOHT7001V	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
MIPFL2501V	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Testing Requirements = Continuous emissions monitoring system in lieu of testing requirements in § 115.725(a).</p>	
MIPFL2501V	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.	
MIPFL2501V	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Designated Grp1 = The emission stream is designated as Group 1.</p> <p>Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control.</p> <p>Designated Hal = The emission stream is not designated as halogenated.</p> <p>Determined Hal = The emission stream is determined to be non-halogenated.</p> <p>Prior Eval = The data from a prior evaluation or assessment is not used.</p> <p>Assessment Waiver = The Administrator has granted a waiver of compliance assessment.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p>	
MPBDM3219	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
MPBFL2502V	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Testing Requirements = Continuous emissions monitoring system in lieu of testing requirements in § 115.725(a).</p>	
MPBFL2502V	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			specifically classified under the rule.	
MPBFL2502V	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
MPBFL2502V	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Designated Grp1 = The emission stream is designated as Group 1.</p> <p>Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control.</p> <p>Designated Hal = The emission stream is not designated as halogenated.</p> <p>Determined Hal = The emission stream is determined to be non-halogenated.</p> <p>Prior Eval = The data from a prior evaluation or assessment is not used.</p> <p>Assessment Waiver = The Administrator has granted a waiver of compliance assessment.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p>	
MPBTK3226	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
MPBTK3226	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OFXR4360AV	30 TAC Chapter 115, HRVOC Vent Gas	R5720-4	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
OFXR4360AV	30 TAC Chapter 115, Vent Gas Controls	R5121-16	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OFXR4360BV	30 TAC Chapter 115, HRVOC Vent Gas	R5720-4	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
OFXR4360BV	30 TAC Chapter	R5121-15	Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, Vent Gas Controls		<p>115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OFXR4360CV	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft3/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Meeting § 115.725(a).</p>	
OFXR4360CV	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1BL803AV	30 TAC Chapter 115, Vent Gas Controls	R5121-34	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP1BL803AV	30 TAC Chapter 115, Vent Gas Controls	R5121-4	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
OP1BL803BV	30 TAC Chapter 115, Vent Gas Controls	R5121-31	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP1BL803BV	30 TAC Chapter 115, Vent Gas Controls	R5121-5	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B,</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
OP1D3626AV	30 TAC Chapter 115, Vent Gas Controls	R5121-10	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1D3626BV	30 TAC Chapter 115, Vent Gas Controls	R5121-11	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1D3635AV	30 TAC Chapter 115, Vent Gas Controls	R5121-12	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B,</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1D3635BV	30 TAC Chapter 115, Vent Gas Controls	R5121-13	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1DECOKE2	30 TAC Chapter 115, Vent Gas Controls	R5121-9	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1DM3420V	30 TAC Chapter 115, Vent Gas Controls	R5121-37	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1DM3422V	30 TAC Chapter 115, Vent Gas Controls	R5121-9	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1FL3801V	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a flare.</p>	
OP1FL3801V	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP1FL3801V	30 TAC Chapter 115, Vent Gas Controls	R5121-32	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP1FL3801V	30 TAC Chapter 115, Vent Gas Controls	R5121-33	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
OP1FL3801V	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Designated Grp1 = The emission stream is designated as Group 1.</p> <p>Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control.</p> <p>Designated Hal = The emission stream is not designated as halogenated.</p> <p>Determined Hal = The emission stream is determined to be non-halogenated.</p> <p>Prior Eval = The data from a prior evaluation or assessment is not used.</p> <p>Assessment Waiver = The Administrator has granted a waiver of compliance assessment.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP1FL3801V	40 CFR Part 63, Subpart G	63G-3	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>	
OP1FL3801V	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP1HT3415	30 TAC Chapter 111, Visible Emissions	R1111-5	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
OP1HT3415	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP1HT3601V	30 TAC Chapter 115, Vent Gas Controls	R5121-33	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP1HT3601V	30 TAC Chapter 115, Vent Gas Controls	R5121-6	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
OP1HT3701V	30 TAC Chapter 115, Vent Gas Controls	R5121-26	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP1HT3701V	30 TAC Chapter 115, Vent Gas Controls	R5121-7	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
OP1PV3804A	30 TAC Chapter 115, Vent Gas Controls	R5121-38	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1PV3804B	30 TAC Chapter 115, Vent Gas Controls	R5121-39	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1RX3701V	30 TAC Chapter 115, Vent Gas Controls	R5121-14	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1RX3702V	30 TAC Chapter 115, Vent Gas Controls	R5121-15	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1SMLTK14	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP1SU3406	30 TAC Chapter 115, Vent Gas Controls	R5121-23	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1SU3406	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP1SU3407	30 TAC Chapter 115, Vent Gas Controls	R5121-24	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1SU3407	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP1SU3502	30 TAC Chapter 115, Vent Gas Controls	R5121-26	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1SU3502	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP1SU3671	30 TAC Chapter 115, Vent Gas Controls	R5121-25	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1SU3671	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP1SU38094	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP1SU38099	30 TAC Chapter 115, Vent Gas Controls	R5121-22	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP1SU38601	30 TAC Chapter 115, Vent Gas Controls	R5121-21	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2BL803AV	30 TAC Chapter 115, Vent Gas Controls	R5121-31	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP2BL803AV	30 TAC Chapter 115, Vent Gas Controls	R5121-7	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
OP2BL803BV	30 TAC Chapter 115, Vent Gas Controls	R5121-32	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP2BL803BV	30 TAC Chapter 115, Vent Gas Controls	R5121-8	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.	
OP2D4626AV	30 TAC Chapter 115, Vent Gas Controls	R5121-11	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2D4626BV	30 TAC Chapter 115, Vent Gas Controls	R5121-12	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2D4635AV	30 TAC Chapter 115, Vent Gas Controls	R5121-13	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2D4635BV	30 TAC Chapter 115, Vent Gas	R5121-14	Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Controls		<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2DECOKE2	30 TAC Chapter 115, Vent Gas Controls	R5121-9	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2DM4420V	30 TAC Chapter 115, Vent Gas Controls	R5121-41	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2DM4422V	30 TAC Chapter 115, Vent Gas Controls	R5121-40	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2FL4801V	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a flare.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Testing Requirements = Continuous emissions monitoring system in lieu of testing requirements in § 115.725(a).</p>	
OP2FL4801V	30 TAC Chapter 115, Vent Gas Controls	R5121-10	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
OP2FL4801V	30 TAC Chapter 115, Vent Gas Controls	R5121-33	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP2FL4801V	30 TAC Chapter 115, Vent Gas Controls	R5121-9	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
OP2FL4801V	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Designated Grp1 = The emission stream is designated as Group 1.</p> <p>Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control.</p> <p>Hal Device Type = No halogen scrubber or other halogen reduction device is used.</p> <p>Designated Hal = The emission stream is not designated as halogenated.</p> <p>Determined Hal = The emission stream is determined to be non-halogenated.</p> <p>Prior Eval = The data from a prior evaluation or assessment is not used.</p> <p>Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver is requested.</p> <p>Prior Eval = The data from a prior evaluation or assessment is not used.</p> <p>Assessment Waiver = The Administrator has granted a waiver of compliance assessment.</p> <p>Formaldehyde = The stream does not contain formaldehyde.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP2FL4801V	40 CFR Part 63, Subpart G	63G-2	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>	
OP2FL4801V	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP2HT4601V	30 TAC Chapter 115, Vent Gas Controls	R5121-10	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>	
OP2HT4601V	30 TAC Chapter 115, Vent Gas Controls	R5121-34	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B,</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP2PV4804A	30 TAC Chapter 115, Vent Gas Controls	R5121-42	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2PV4804B	30 TAC Chapter 115, Vent Gas Controls	R5121-43	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2RX4701V	30 TAC Chapter 115, Vent Gas Controls	R5121-17	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP2RX4703V	30 TAC Chapter 115, Vent Gas Controls	R5121-18	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2SU4406	30 TAC Chapter 115, Vent Gas Controls	R5121-26	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2SU4407	30 TAC Chapter 115, Vent Gas Controls	R5121-27	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2SU4502	30 TAC Chapter 115, Vent Gas Controls	R5121-29	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B,</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2SU4502	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP2SU4671	30 TAC Chapter 115, Vent Gas Controls	R5121-19	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Carbon adsorption system that replaces the carbon at a predetermined time interval.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
OP2SU4671	40 CFR Part 63, Subpart YY	63YY-1	Source Type = Ethylene production	
OP2SU48099	30 TAC Chapter 115, Vent Gas Controls	R5121-25	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
OP2SU48601	30 TAC Chapter 115, Vent Gas Controls	R5121-21	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
ZMSZZCOAT	30 TAC Chapter 115, Surface Coating Operations	R5421-1	<p>Alternative Compliance Method = No alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria has been approved by the TCEQ Executive Director or no such alternate has been requested.</p> <p>Facility Operations = Surface coating of wood parts and products.</p> <p>VOC Emission Rate = Uncontrolled emission rates not qualifying for exemption from control.</p> <p>Vapor Recovery = No vapor recovery system is used to control emissions.</p> <p>Wood Coating Type = Enamel or opaque ground coat.</p>	
ZMSZZCOAT	30 TAC Chapter 115, Surface Coating Operations	R5421-2	<p>Alternative Compliance Method = No alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria has been approved by the TCEQ Executive Director or no such alternate has been requested.</p> <p>Facility Operations = Surface coating of wood parts and products.</p> <p>VOC Emission Rate = Uncontrolled emission rates not qualifying for exemption from control.</p> <p>Vapor Recovery = No vapor recovery system is used to control emissions.</p> <p>Wood Coating Type = Semitransparent wiping or glazing stain.</p>	
ZMSZZCOAT	30 TAC Chapter 115, Surface Coating Operations	R5421-3	<p>Alternate Requirements = No alternate requirement to 30 TAC §§ 115.421(a)(9) or 115.421(b)(8) has been approved or no alternate has been requested.</p> <p>Alternative Compliance Method = No alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria has been approved by the TCEQ Executive Director or no such alternate has been requested.</p> <p>Facility Operations = Other miscellaneous metal parts and products coating.</p> <p>Miscellaneous Coating Type = Extreme performance coating, including chemical milling maskants.</p> <p>Maintenance Shop = Recoating used miscellaneous metal parts and products at an on-site maintenance shop that began operations before January 1, 2012.</p> <p>VOC Emission Rate = Uncontrolled emission rates not qualifying for exemption from control.</p> <p>Vapor Recovery = No vapor recovery system is used to control emissions.</p>	
EUTDM01086	30 TAC Chapter 115, Industrial Wastewater	R5140-16A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM01086	30 TAC Chapter 115, Industrial Wastewater	R5140-16B	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM01086	30 TAC Chapter 115, Industrial Wastewater	R5140-16C	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM0701	30 TAC Chapter 115, Industrial Wastewater	R5140-16A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM0701	30 TAC Chapter 115, Industrial Wastewater	R5140-16B	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM0701	30 TAC Chapter 115, Industrial Wastewater	R5140-16C	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM0801	30 TAC Chapter 115, Industrial Wastewater	R5140-16A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM0801	30 TAC Chapter 115, Industrial Wastewater	R5140-16B	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM0801	30 TAC Chapter 115, Industrial Wastewater	R5140-16C	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM8801	30 TAC Chapter 115, Industrial Wastewater	R5140-16A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM8801	30 TAC Chapter 115, Industrial Wastewater	R5140-16B	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM8801	30 TAC Chapter 115, Industrial Wastewater	R5140-16C	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM8804	30 TAC Chapter 115, Industrial Wastewater	R5140-16A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>§ 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM8804	30 TAC Chapter 115, Industrial Wastewater	R5140-16B	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTDM8804	30 TAC Chapter 115, Industrial Wastewater	R5140-16C	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTTK88014	30 TAC Chapter 115, Industrial Wastewater	R5140-16A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTTK88014	30 TAC Chapter 115, Industrial Wastewater	R5140-16B	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTTK88014	30 TAC Chapter 115, Industrial Wastewater	R5140-16C	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTTW8801	30 TAC Chapter 115, Industrial Wastewater	R5140-17A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Steam stripper.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTTW8801	30 TAC Chapter 115, Industrial Wastewater	R5140-17B	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EUTTW8801	30 TAC Chapter 115, Industrial Wastewater	R5140-17C	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTTW8802	30 TAC Chapter 115, Industrial Wastewater	R5140-18A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Steam stripper.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTTW8802	30 TAC Chapter 115, Industrial Wastewater	R5140-18B	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EUTTW8802	30 TAC Chapter 115, Industrial Wastewater	R5140-18C	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Devices = Flare.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
GRPOP1TK1	30 TAC Chapter 115, Industrial Wastewater	R5140-8	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
GRPOP1TK6	30 TAC Chapter 115, Industrial Wastewater	R5140-3	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
GRPOP2TK6	30 TAC Chapter 115, Industrial Wastewater	R5140-3	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP1SU38094	30 TAC Chapter 115, Industrial Wastewater	R5140-6	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Enclosed combustion device.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP1TK3455	30 TAC Chapter 115, Industrial Wastewater	R5140-15	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP1TK3458	30 TAC Chapter 115, Industrial Wastewater	R5140-6	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Enclosed combustion device.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP1TK38008	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP1TK38009	30 TAC Chapter 115, Industrial Wastewater	R5140-2	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP1TK3903	30 TAC Chapter 115, Industrial Wastewater	R5140-16A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP2SU48094	30 TAC Chapter 115, Industrial Wastewater	R5140-6	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = The wastewater component does not have a floating roof or internal floating roof.</p> <p>Control Devices = Enclosed combustion device.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Monitoring Type = The monitoring requirements of 30 TAC §§ 115.144(3)(A) - (H) are being used.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP2TK4455	30 TAC Chapter 115, Industrial Wastewater	R5140-6	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP2TK4458	30 TAC Chapter 115, Industrial Wastewater	R5140-6	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP2TK48008	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
OP2TK48009	30 TAC Chapter 115, Industrial Wastewater	R5140-1	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = The component is not a wet weather retention basin, exempted by §115.147(2), not a biotreatment unit.</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>Roof or Seal Type = Floating roof or internal floating roof wastewater component tank that does not have a vapor mounted</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
WASTEWATER	30 TAC Chapter 115, Industrial Wastewater	R5140-16A	<p>Petroleum Refinery = The affected source category is not a petroleum refinery.</p> <p>Wastewater Component Type = A wastewater component that is exempted from the control requirements of 30 TAC § 115.142 because it handles only exempted wastewater streams under 30 TAC § 115.147(2).</p> <p>Alternate Control Requirement = An alternate control requirement (ACR) or exemption criteria in accordance with 30 TAC § 115.910 is not used.</p> <p>90% Overall Control Option = The unit is complying with the control requirements of 30 TAC § 115.142.</p> <p>Safety Hazard Exemption = No safety hazard exemption has been requested or none has been approved.</p>	
EBGVC6904	30 TAC Chapter 117, Subchapter B	R7300-9	<p>Fuel Flow Monitoring = Fuel flow is with a totalizing fuel flow meter per 30 TAC §§ 117.340(a) or 117.440(a)</p> <p>Maximum Rated Capacity = MRC is greater than 40 MMBtu/hr but less than 100 MMBtu/hr</p> <p>CO Emission Limitation = Complying with 30 TAC § 117.310(c)(1)</p> <p>NOx Emission Limitation = Complying with 30 TAC § 117.310(a)(16)</p> <p>CO Monitoring System = Sampling CO with a portable analyzer under 30 TAC § 117.8120(2)</p> <p>NOx Reduction = No NO_x reduction method</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			NOx Monitoring System = Maximum emission rate testing	
EC4TO	30 TAC Chapter 117, Subchapter B	R7ICI-23	Maximum Rated Capacity = MRC is less than 40 MMBtu/hr	
GRPC4RXR2	40 CFR Part 60, Subpart RRR	60RRR-1A	<p>Chemicals Listed in 40 CFR § 60.707 = The affected facility is part of a process unit that produces chemicals listed in 40 CFR § 60.707 as a product, co-product, by product, or intermediate.</p> <p>Construction/Modification Date = After June 29, 1990.</p> <p>Affected Facility Type = Combination of a reactor process and the recovery system into which its vent stream is discharged.</p> <p>Subject to Title 40 CFR Part 60, Subpart DDD = The reactor process is not subject to the provisions of Title 40 CFR Part 60, Subpart DDD.</p> <p>Subject to Title 40 CFR Part 60, Subpart NNN = The vent stream is routed to a distillation unit subject to Title 40 CFR Part 60, Subpart NNN and has no other releases to the air except for a pressure relief valve.</p>	
EUTTW8801	40 CFR Part 63, Subpart G	63G-30A	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Design steam stripper option.</p> <p>Control Devices = Flare.</p>	
EUTTW8801	40 CFR Part 63, Subpart G	63G-30B	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Designated as Group 1 per 40 CFR § 63.132(e).</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Design steam stripper option.</p> <p>Control Devices = Flare.</p>	
EUTTW8801	40 CFR Part 63, Subpart G	63G-30C	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Design steam stripper option.</p> <p>Control Devices = Flare.</p>	
EUTTW8801	40 CFR Part 63, Subpart G	63G-30D	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Designated as Group 1 per 40 CFR § 63.132(e).</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Design steam stripper option.</p> <p>Control Devices = Flare.</p>	
EUTTW8802	40 CFR Part 63, Subpart G	63G-30A	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR §</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Design steam stripper option.</p> <p>Control Devices = Flare.</p>	
EUTTW8802	40 CFR Part 63, Subpart G	63G-30B	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Designated as Group 1 per 40 CFR § 63.132(e).</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Design steam stripper option.</p> <p>Control Devices = Flare.</p>	
EUTTW8802	40 CFR Part 63, Subpart G	63G-30C	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Design steam stripper option.</p> <p>Control Devices = Flare.</p>	
EUTTW8802	40 CFR Part 63, Subpart G	63G-30D	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Designated as Group 1 per 40 CFR § 63.132(e).</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Design steam stripper option.</p> <p>Control Devices = Flare.</p>	
GRPBZTW	40 CFR Part 61, Subpart FF	61FF-8A	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Treatment Stream Unit Exempt = There are not units in the wastewater treatment system that are exempt according to 40 CFR § 61.348(b)(2).</p> <p>Complying with § 61.342(e) = The facility is not complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Flare.</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Stream Combination = The process wastewater, product tank drawdown, or landfill leachate is combined with other waste streams for the purpose of facilitating management or treatment in the wastewater treatment system.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Engineering calculations show that the treatment process or wastewater treatment system unit is proven to achieve its emission limitation.</p>	
GRPBZTW	40 CFR Part 61, Subpart FF	61FF-8B	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Treatment Stream Unit Exempt = There are not units in the wastewater treatment system that are exempt according to 40 CFR § 61.348(b)(2).</p> <p>Complying with § 61.342(e) = The facility is not complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Flare.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Stream Combination = The process wastewater, product tank drawdown, or landfill leachate is combined with other waste streams for the purpose of facilitating management or treatment in the wastewater treatment system.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Engineering calculations show that the treatment process or wastewater treatment system unit is proven to achieve its emission limitation.</p>	
GRPBZTW	40 CFR Part 61, Subpart FF	61FF-8C	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Treatment Stream Unit Exempt = There are not units in the wastewater treatment system that are exempt according to 40 CFR § 61.348(b)(2).</p> <p>Complying with § 61.342(e) = The facility is not complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Flare.</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Stream Combination = The process wastewater, product tank drawdown, or landfill leachate is combined with other waste streams for the purpose of facilitating management or treatment in the wastewater treatment system.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Performance tests are used to show that the treatment process or wastewater treatment system unit achieves its emission limitation.</p>	
GRPBZTW	40 CFR Part 61, Subpart FF	61FF-8D	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Treatment Stream Unit Exempt = There are not units in the wastewater treatment system that are exempt according to 40 CFR § 61.348(b)(2).</p> <p>Complying with § 61.342(e) = The facility is not complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Flare.</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Stream Combination = The process wastewater, product tank drawdown, or landfill leachate is combined with other waste streams for the purpose of facilitating management or treatment in the wastewater treatment system.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Performance tests are used to show that the treatment process or wastewater treatment system unit achieves its emission limitation.</p>	
GRPBZTW	40 CFR Part 63, Subpart G	63G-7A	<p>Combustion Process = No combustion process is used for treatment.</p> <p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value.</p> <p>Control Devices = Flare.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated using design evaluation.</p>	
GRPBZTW	40 CFR Part 63, Subpart G	63G-7B	<p>Combustion Process = No combustion process is used for treatment.</p> <p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value.</p> <p>Control Devices = Flare.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated by performance test.</p>	
GRPBZTW	40 CFR Part 63, Subpart G	63G-7C	<p>Combustion Process = No combustion process is used for treatment.</p> <p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value.</p> <p>Control Devices = Flare.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated using design evaluation.</p>	
GRPBZTW	40 CFR Part 63, Subpart G	63G-7D	<p>Combustion Process = No combustion process is used for treatment.</p> <p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value.</p> <p>Control Devices = Flare.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated by performance</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			test.	
GRPBZTW	40 CFR Part 63, Subpart YY	63YY-1	Facility Type = ETHYLENE PRODUCTION FACILITY	
OP1TW3407	40 CFR Part 61, Subpart FF	61FF-1A	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Treatment Stream Unit Exempt = There are not units in the wastewater treatment system that are exempt according to 40 CFR § 61.348(b)(2).</p> <p>Complying with § 61.342(e) = The facility is not complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Flare.</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Stream Combination = The process wastewater, product tank drawdown, or landfill leachate is combined with other waste streams for the purpose of facilitating management or treatment in the wastewater treatment system.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Engineering calculations show that the treatment process or wastewater treatment system unit is proven to achieve its emission limitation.</p>	
OP1TW3407	40 CFR Part 61, Subpart FF	61FF-1B	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Treatment Stream Unit Exempt = There are not units in the wastewater treatment system that are exempt according to 40 CFR § 61.348(b)(2).</p> <p>Complying with § 61.342(e) = The facility is not complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Flare.</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Stream Combination = The process wastewater, product tank drawdown, or landfill leachate is combined with other waste streams for the purpose of facilitating management or treatment in the wastewater treatment system.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Engineering calculations show that the treatment process or wastewater treatment system unit is proven to achieve its emission limitation.</p>	
OP1TW3407	40 CFR Part 61, Subpart FF	61FF-1C	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Continuous Monitoring = The wastewater treatment system unit process parameters are continuously monitored to indicate proper system operation.</p> <p>Treatment Stream Unit Exempt = There are not units in the wastewater treatment system that are exempt according to 40 CFR § 61.348(b)(2).</p> <p>Complying with § 61.342(e) = The facility is not complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Flare.</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Stream Combination = The process wastewater, product tank drawdown, or landfill leachate is combined with other waste streams for the purpose of facilitating management or treatment in the wastewater treatment system.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Performance tests are used to show that the treatment process or wastewater treatment system unit achieves its emission limitation.</p>	
OP1TW3407	40 CFR Part 61, Subpart FF	61FF-1D	<p>AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used.</p> <p>By-Pass Line = The closed-vent system does not contain a by-pass line that could divert the vent stream away from the control device.</p> <p>Continuous Monitoring = The wastewater treatment system unit process parameters are continuously monitored to indicate proper system operation.</p> <p>Treatment Stream Unit Exempt = There are not units in the wastewater treatment system that are exempt according to 40 CFR § 61.348(b)(2).</p> <p>Complying with § 61.342(e) = The facility is not complying with 40 CFR § 61.342(e).</p> <p>Control Device Type/Operation = Flare.</p> <p>Openings = The treatment process or wastewater treatment system unit has no openings.</p> <p>Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system.</p> <p>Stream Combination = The process wastewater, product tank drawdown, or landfill leachate is combined with other</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>waste streams for the purpose of facilitating management or treatment in the wastewater treatment system.</p> <p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Performance tests are used to show that the treatment process or wastewater treatment system unit achieves its emission limitation.</p>	
OP1TW3407	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>Halogenated = The stream is determined as non-halogenated.</p> <p>Series Of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Vented To Control = Emissions from the treatment process are vented to a control device.</p> <p>Alt 63G Mon Parameters = The EPA Administrator has not approved an alternate monitoring parameter or no alternate has been requested.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated using performance tests.</p> <p>By-pass Lines = No by-pass lines.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Combination Of Control Devices = The vent stream is treated using a single control device.</p> <p>Combustion Process = No combustion process is used for treatment.</p> <p>Control Devices = Flare.</p> <p>Wastewater Stream Designation = The wastewater stream is designated as Group 1 per 40 CFR § 63.132(e).</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value per 40 CFR § 63.138(e)(2).</p>	
OP1TW3407	40 CFR Part 63, Subpart FFFF	63FFFF-2	<p>Halogenated = The stream is determined as non-halogenated.</p> <p>Series Of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Vented To Control = Emissions from the treatment process are vented to a control device.</p> <p>Alt 63G Mon Parameters = The EPA Administrator has not approved an alternate monitoring parameter or no alternate has been requested.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated using performance tests.</p> <p>By-pass Lines = No by-pass lines.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Combination Of Control Devices = The vent stream is treated using a single control device.</p> <p>Combustion Process = No combustion process is used for treatment.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Devices = Flare.</p> <p>Wastewater Stream Designation = The wastewater stream is designated as Group 1 per 40 CFR § 63.132(e).</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value per 40 CFR § 63.138(e)(2).</p>	
OP1TW3407	40 CFR Part 63, Subpart G	63G-7A	<p>Combustion Process = No combustion process is used for treatment.</p> <p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value.</p> <p>Control Devices = Flare.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated using design evaluation.</p>	
OP1TW3407	40 CFR Part 63, Subpart G	63G-7B	<p>Combustion Process = No combustion process is used for treatment.</p> <p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value.</p> <p>Control Devices = Flare.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated by performance test.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
OP1TW3407	40 CFR Part 63, Subpart G	63G-7C	<p>Combustion Process = No combustion process is used for treatment.</p> <p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value.</p> <p>Control Devices = Flare.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated using design evaluation.</p>	
OP1TW3407	40 CFR Part 63, Subpart G	63G-7D	<p>Combustion Process = No combustion process is used for treatment.</p> <p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.172.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Percent removal/destruction option by reducing the mass flow rate by the Fr value.</p> <p>Control Devices = Flare.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated by performance test.</p>	
OP1TW3407	40 CFR Part 63, Subpart YY	63YY-1	Facility Type = ETHYLENE PRODUCTION FACILITY	
PRO-ALKY	40 CFR Part 63, Subpart FFFF	63FFFF-1	>1000 lb/yr = The process has uncontrolled hydrogen halide and halogen HAP emissions from process vents of less than 1,000 lb/yr.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Ammonium Sulfate = The MCPU does not include the manufacture of ammonium sulfate as a by-product, or the slurry entering the by-product manufacturing process contains 50 parts per million by weight (ppmw) HAP or less or 10 ppmw benzene or less.</p> <p>Startup 2003 = The affected source startup was before November 10, 2003.</p> <p>Other Operations = The MCPU includes operations other than those listed in § 63.2435(c).</p> <p>Shared Batch Vent = The MCPU does not include a batch process vent that also is part of a CMPU as defined in subparts F and G of this part 63.</p> <p>63.100 CMPU = The MCPU is not a CMPU defined in § 63.100.</p> <p>New Source = The MCPU is an existing affected source.</p> <p>PUG = The MCPU is not part of a process unit group (PUG).</p> <p>G2/<1000 lb/yr = The process does not include Group 2 batch process vents and/or uncontrolled hydrogen halide and halogen HAP emissions from the sum of all batch and continuous process vents less than 1,000 lb/yr.</p> <p>Startup 2002 = The affected source initial startup was before April 4, 2002.</p> <p>PP Alt = The MCPU is complying with the emission limitations and work practice standards contained in Tables 1 through 7.</p> <p>Batch Process Vents = The source does not include batch process vents.</p>	
PRO-BT	40 CFR Part 63, Subpart F	63F-1	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.</p>	
PRO-C4	40 CFR Part 63, Subpart F	63F-1	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.</p>	
PRO-C5	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>>1000 lb/yr = The process has uncontrolled hydrogen halide and halogen HAP emissions from process vents of less than 1,000 lb/yr.</p> <p>Ammonium Sulfate = The MCPU does not include the manufacture of ammonium sulfate as a by-product, or the slurry entering the by-product manufacturing process contains 50 parts per million by weight (ppmw) HAP or less or 10 ppmw benzene or less.</p> <p>Startup 2003 = The affected source startup was before November 10, 2003.</p> <p>Other Operations = The MCPU includes operations other than those listed in § 63.2435(c).</p> <p>Shared Batch Vent = The MCPU does not include a batch process vent that also is part of a CMPU as defined in subparts F and G of this part 63.</p> <p>63.100 CMPU = The MCPU is not a CMPU defined in § 63.100.</p> <p>New Source = The MCPU is an existing affected source.</p> <p>PUG = The MCPU is not part of a process unit group (PUG).</p> <p>G2/<1000 lb/yr = The process does not include Group 2 batch process vents and/or uncontrolled hydrogen halide and halogen HAP emissions from the sum of all batch and continuous process vents less than 1,000 lb/yr.</p> <p>Startup 2002 = The affected source initial startup was before April 4, 2002.</p> <p>PP Alt = The MCPU is complying with the emission limitations and work practice standards contained in Tables 1 through 7.</p> <p>Batch Process Vents = The source does not include batch process vents.</p>	
PRO-DPG	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>>1000 lb/yr = The process has uncontrolled hydrogen halide and halogen HAP emissions from process vents of less than 1,000 lb/yr.</p> <p>Ammonium Sulfate = The MCPU does not include the manufacture of ammonium sulfate as a by-product, or the slurry entering the by-product manufacturing process contains 50 parts per million by weight (ppmw) HAP or less or 10 ppmw</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>benzene or less.</p> <p>Startup 2003 = The affected source startup was before November 10, 2003.</p> <p>Other Operations = The MCPU includes operations other than those listed in § 63.2435(c).</p> <p>Shared Batch Vent = The MCPU does not include a batch process vent that also is part of a CMPU as defined in subparts F and G of this part 63.</p> <p>63.100 CMPU = The MCPU is not a CMPU defined in § 63.100.</p> <p>New Source = The MCPU is an existing affected source.</p> <p>PUG = The MCPU is not part of a process unit group (PUG).</p> <p>G2/<1000 lb/yr = The process does not include Group 2 batch process vents and/or uncontrolled hydrogen halide and halogen HAP emissions from the sum of all batch and continuous process vents less than 1,000 lb/yr.</p> <p>Startup 2002 = The affected source initial startup was before April 4, 2002.</p> <p>PP Alt = The MCPU is complying with the emission limitations and work practice standards contained in Tables 1 through 7.</p> <p>Batch Process Vents = The source does not include batch process vents.</p>	
PRO-FLEX	40 CFR Part 63, Subpart YY	63YY-1	<p>Research and Development = THE PROCESS UNIT IS USED IN PRODUCTION</p> <p>Flexible Unit = THE PROCESS UNIT IS DEDICATED TO ONE PRODUCT</p> <p>Primary Product = THE PRIMARY PRODUCT OF THE PROCESS UNIT IS A PRODUCT PRODUCED BY A REGULATED SOURCE CATEGORY</p> <p>Source Category = ETHYLENE PRODUCTION</p>	
PRO-IPOH	40 CFR Part 63, Subpart FFFF	63FFFF-1	<p>>1000 lb/yr = The process has uncontrolled hydrogen halide and halogen HAP emissions from process vents of less than 1,000 lb/yr.</p> <p>Ammonium Sulfate = The MCPU does not include the manufacture of ammonium sulfate as a by-product, or the slurry entering the by-product manufacturing process contains 50 parts per million by weight (ppmw) HAP or less or 10 ppmw benzene or less.</p> <p>Startup 2003 = The affected source startup was before November 10, 2003.</p> <p>Other Operations = The MCPU includes operations other than those listed in § 63.2435(c).</p> <p>Shared Batch Vent = The MCPU does not include a batch process vent that also is part of a CMPU as defined in subparts F and G of this part 63.</p> <p>63.100 CMPU = The MCPU is not a CMPU defined in § 63.100.</p> <p>New Source = The MCPU is an existing affected source.</p> <p>PUG = The MCPU is not part of a process unit group (PUG).</p> <p>G2/<1000 lb/yr = The process does not include Group 2 batch process vents and/or uncontrolled hydrogen halide and halogen HAP emissions from the sum of all batch and continuous process vents less than 1,000 lb/yr.</p> <p>Startup 2002 = The affected source initial startup was before April 4, 2002.</p> <p>PP Alt = The MCPU is complying with the emission limitations and work practice standards contained in Tables 1 through 7.</p> <p>Batch Process Vents = The source does not include batch process vents.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
PRO-MEO	40 CFR Part 63, Subpart F	63F-1	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.</p>	
PRO-MTBE	40 CFR Part 63, Subpart F	63F-1	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			side at least 35 kilopascals greater than the maximum pressure on the process side.	
PRO-OP1	40 CFR Part 63, Subpart YY	63YY-1	Research and Development = THE PROCESS UNIT IS USED IN PRODUCTION Flexible Unit = THE PROCESS UNIT IS DEDICATED TO ONE PRODUCT Primary Product = THE PRIMARY PRODUCT OF THE PROCESS UNIT IS A PRODUCT PRODUCED BY A REGULATED SOURCE CATEGORY Source Category = ETHYLENE PRODUCTION	
PRO-OP2	40 CFR Part 63, Subpart YY	63YY-1	Research and Development = THE PROCESS UNIT IS USED IN PRODUCTION Flexible Unit = THE PROCESS UNIT IS DEDICATED TO ONE PRODUCT Primary Product = THE PRIMARY PRODUCT OF THE PROCESS UNIT IS A PRODUCT PRODUCED BY A REGULATED SOURCE CATEGORY Source Category = ETHYLENE PRODUCTION	
PRO-POLYBD	40 CFR Part 63, Subpart FFFF	63FFFF-1	>1000 lb/yr = The process has uncontrolled hydrogen halide and halogen HAP emissions from process vents of less than 1,000 lb/yr. Ammonium Sulfate = The MCPU does not include the manufacture of ammonium sulfate as a by-product, or the slurry entering the by-product manufacturing process contains 50 parts per million by weight (ppmw) HAP or less or 10 ppmw benzene or less. Startup 2003 = The affected source startup was before November 10, 2003. Other Operations = The MCPU includes operations other than those listed in § 63.2435(c). Shared Batch Vent = The MCPU does not include a batch process vent that also is part of a CMPU as defined in subparts F and G of this part 63. 63.100 CMPU = The MCPU is not a CMPU defined in § 63.100. New Source = The MCPU is an existing affected source. PUG = The MCPU is not part of a process unit group (PUG). G2/<1000 lb/yr = The process does not include Group 2 batch process vents and/or uncontrolled hydrogen halide and halogen HAP emissions from the sum of all batch and continuous process vents less than 1,000 lb/yr. Startup 2002 = The affected source initial startup was before April 4, 2002. PP Alt = The MCPU is complying with the emission limitations and work practice standards contained in Tables 1 through 7. Batch Process Vents = The source includes batch process vents.	
PRO-SMA	40 CFR Part 63, Subpart FFFF	63FFFF-1	>1000 lb/yr = The process has uncontrolled hydrogen halide and halogen HAP emissions from process vents of less than 1,000 lb/yr. Ammonium Sulfate = The MCPU does not include the manufacture of ammonium sulfate as a by-product, or the slurry entering the by-product manufacturing process contains 50 parts per million by weight (ppmw) HAP or less or 10 ppmw benzene or less. Startup 2003 = The affected source startup was before November 10, 2003. Other Operations = The MCPU includes operations other than those listed in § 63.2435(c). Shared Batch Vent = The MCPU does not include a batch process vent that also is part of a CMPU as defined in	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>subparts F and G of this part 63.</p> <p>63.100 MCPU = The MCPU is not a CPMU defined in § 63.100.</p> <p>New Source = The MCPU is an existing affected source.</p> <p>PUG = The MCPU is not part of a process unit group (PUG).</p> <p>G2/<1000 lb/yr = The process does not include Group 2 batch process vents and/or uncontrolled hydrogen halide and halogen HAP emissions from the sum of all batch and continuous process vents less than 1,000 lb/yr.</p> <p>Startup 2002 = The affected source initial startup was before April 4, 2002.</p> <p>PP Alt = The MCPU is complying with the emission limitations and work practice standards contained in Tables 1 through 7.</p> <p>Batch Process Vents = The source does not include batch process vents.</p>	

* - The "unit attributes" or operating conditions that determine what requirements apply

** - Notes changes made to the automated results from the DSS, and a brief explanation why

NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room,

located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site.

The status of air permits and applications can be found by performing the appropriate search of the databases found at the following website:

www.tceq.texas.gov/permitting/air/nav/air_status_permits.html

New Source Review Authorization References

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: PSDTX1270	Issuance Date: 09/22/2017
PSD Permit No.: PSDTX1272	Issuance Date: 09/22/2017
PSD Permit No.: PSDTX1280M1	Issuance Date: 09/14/2017
PSD Permit No.: PSD-TX-1272-GHG	Issuance Date: 07/19/2013
PSD Permit No.: PSD-TX-1280-GHG	Issuance Date: 02/14/2013
Nonattainment (NA) Permits	
NA Permit No.: N140	Issuance Date: 09/22/2017
NA Permit No.: N142	Issuance Date: 09/22/2017
NA Permit No.: N144	Issuance Date: 09/14/2017
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 111666	Issuance Date: 07/18/2014
Authorization No.: 143753	Issuance Date: 12/22/2016
Authorization No.: 144030	Issuance Date: 01/13/2017
Authorization No.: 146636	Issuance Date: 06/08/2017
Authorization No.: 1768	Issuance Date: 09/22/2017
Authorization No.: 2128	Issuance Date: 05/09/2016
Authorization No.: 22779	Issuance Date: 01/29/2015
Authorization No.: 24677	Issuance Date: 03/14/2016
Authorization No.: 24887	Issuance Date: 11/21/2016
Authorization No.: 2933	Issuance Date: 09/22/2017
Authorization No.: 2936	Issuance Date: 12/21/2012
Authorization No.: 3130A	Issuance Date: 09/02/2015
Authorization No.: 49120	Issuance Date: 01/03/2008
Authorization No.: 49130	Issuance Date: 09/23/2014
Authorization No.: 6245	Issuance Date: 06/10/2005
Authorization No.: 6387	Issuance Date: 06/27/2011

New Source Review Authorization References

Authorization No.: 75881	Issuance Date: 06/23/2015
Authorization No.: 77318	Issuance Date: 01/13/2016
Authorization No.: 8125	Issuance Date: 09/14/2017
Authorization No.: 83799	Issuance Date: 04/07/2014
Authorization No.: 84079	Issuance Date: 05/25/2017
Authorization No.: 84091	Issuance Date: 05/23/2017
Authorization No.: 148067	Issuance Date: 10/05/2017
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.183	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 12/24/1998
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 12/24/1998
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.264	Version No./Date: 09/04/2000
Number: 106.265	Version No./Date: 09/04/2000
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.394	Version No./Date: 09/04/2000
Number: 106.412	Version No./Date: 09/04/2000
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.452	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 03/14/1997
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.474	Version No./Date: 09/04/2000
Number: 106.475	Version No./Date: 09/04/2000
Number: 106.476	Version No./Date: 09/04/2000
Number: 106.477	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 03/14/1997
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.492	Version No./Date: 09/04/2000
Number: 106.495	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000

New Source Review Authorization References

Number: 106.512	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 06/13/2001
Number: 106.532	Version No./Date: 09/04/2000
Number: 106.533	Version No./Date: 09/04/2000
Number: 7	Version No./Date: 05/04/1994
Number: 7	Version No./Date: 04/05/1995
Number: 51	Version No./Date: 09/12/1989
Number: 118	Version No./Date: 09/12/1989
Number: 118	Version No./Date: 06/07/1996

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sand-blasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the "Maximum Allowable Emission Rate Table", or "MAERT" for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit's compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected

Compliance Assurance Monitoring (CAM):

Compliance Assurance Monitoring (CAM) is a federal monitoring program established under Title 40 Code of Federal Regulations Part 64 (40 CFR Part 64).

Emission units are subject to CAM requirements if they meet the following criteria:

1. the emission unit is subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement;
2. the emission unit uses a control device to achieve compliance with the emission limitation or standard specified in the applicable requirement; and
3. the emission unit has the pre-control device potential to emit greater than or equal to the amount in tons per year for a site to be classified as a major source.

The following table(s) identify the emission unit(s) that are subject to CAM:

Unit/Group/Process Information	
ID No.: GRPLDBGDK	
Control Device ID No.: EBGVC6904	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-2
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per day	
Averaging Period: N/A	
Deviation Limit: The presence of visible emissions is a deviation unless visible emissions are determined consistent with Test Method 22 or Test Method 9 and found in compliance with 30 TAC 111.111(a)(4)(A).	
Basis of CAM: NSR Permit No. 3130A Special Condition No. 2 states the vapors from barge loading operations shall be routed to a combustion device (flare) with no less than 98.0 percent destruction efficiency of hydrocarbons. This vapor combustion device shall operate as specified in New Source Performance Standards (NSPS), Title 40 Code of Federal Regulations Part 60.18 (40 CFR Part 60.18). It is widely practiced and accepted to monitor flares by visual inspection for visible emissions and have the option to perform visible emissions readings to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Visible emissions observations indicate that the flare is not efficiently combusting the emissions or there is incomplete combustion. Visible emissions can indicate an improper inlet flow rate or net heating value of the emissions routed to the flare. Monitoring visible emissions is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart A; 30 TAC Chapter 111; and 30 TAC Chapter 115. This procedure is consistent with the EPA "CAM Technical Document" (August 1998) which provides an example of using "EPA Test Method 22-like" procedures for determining visible emissions.	

Periodic Monitoring:

The Federal Clean Air Act requires that each federal operating permit include monitoring sufficient to assure compliance with the terms and conditions of the permit. Most of the emission limits and standards applicable to emission units at Title V sources include adequate monitoring to show that the units meet the limits and standards. For those requirements that do not include monitoring, or where the monitoring is not sufficient to assure compliance, the federal operating permit must include such monitoring for the emission units affected. The following emission units are subject to periodic monitoring requirements because the emission units are subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement that does not already require monitoring, or the monitoring for the applicable requirement is not sufficient to assure compliance:

Unit/Group/Process Information	
ID No.: EALSP4066	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 30% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: EC4HT1202	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-6
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations. The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: EC4TO	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 20% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations. The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: EC5SP334	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 30% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: EC5SP349	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 30% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: EC5TK36	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-5
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: EC5TK36	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-5
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: GRPBOILER	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart D	SOP Index No.: 60D-1A
Pollutant: PM	Main Standard: § 60.42(a)(1)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 15% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: GRPLIQFURN	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-5
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 15% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: GRPOLFUR2V	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Visible emissions opacity reading greater than 15%.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: GRPOLFURN	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-3
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 15% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: GRPOLSUHT	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-4
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 15% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: GRPOLTKIFR	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-3A
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric and repairs are not completed.	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: GRPOP1TK1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1A
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: Annually	
Averaging Period: N/A	
<p>Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the floating roof, the seals are detached, or if there are holes or tears in the seal fabric and repairs are not completed.</p>	
<p>Basis of monitoring: The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: GRPOP2TK1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-2A
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: Annually	
Averaging Period: N/A	
<p>Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the floating roof, the seals are detached, or if there are holes or tears in the seal fabric and repairs are not completed.</p>	
<p>Basis of monitoring: The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: GRPSMAPMV	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 30% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: MEOHT7001V	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Visible emissions opacity reading greater than 15%.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: MIPTK3110	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-4
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: MIPTK3110	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-4
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: MPBDM3219	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 30% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: MPBDM3219	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: MPBDM3219	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: MPBTK3210	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: MPBTK3210	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: MPBTK3226	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 30% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: OFXDM4310	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OFXDM4310	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OFXDM4311	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OFXDM4311	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP1HT3415	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-5
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 15% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: OP1TK3601	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-6
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP1TK3601	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-6
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP1TK3911	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-4
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the floating roof, the seals are detached, or if there are holes or tears in the seal fabric and repairs are not completed.	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: OP1TK3912	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-5
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the floating roof, the seals are detached, or if there are holes or tears in the seal fabric and repairs are not completed as specified.	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4456	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-10
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4456	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-10
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4458	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4458	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4465	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Fill pipe not integral and not repaired before refill is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4465	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4601	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-9
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It is a deviation if the fill pipe is damaged and not repaired.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4601	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-9
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Fill pipe not submerged in liquid is a deviation.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4901	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1A
Pollutant: VOC	Main Standard: § 60.110(c)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the floating roof, the seals are detached, or if there are holes or tears in the seal fabric and repairs are not completed.	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: OP2TK4921	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-4A
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the floating roof, the seals are detached, or if there are holes or tears in the seal fabric and repairs are not completed as specified.	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Obtaining Permit Documents

The New Source Review Authorization References table in the FOP specifies all NSR permits that apply at the permit area covered by the FOP. This includes permits by rule. Individual NSR permitting files are located in the TCEQ Central File Room (TCEQ Main Campus located at 12100 Park 35 Circle, Austin, Texas, 78753, Building E, Room 103). Also, TCEQ has developed a website based mechanism to electronically access public documents. TCEQ's Central File Room Online website (<https://www.tceq.texas.gov/goto/cfr-online>) should be used for all electronic document searches. Guidance documents that describe how to search electronic records archived in the Central File Room server are available at

https://www.tceq.texas.gov/permitting/air/nav/air_status_permits.html

All current permits by rule are contained in Chapter 106 and can be viewed at the following website:

https://www.tceq.texas.gov/permitting/air/permitbyrule/air_pbr_index.html

Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following website:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html

Outdated Standard Exemption lists may be viewed at the following website:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

Additional information concerning PBRs is available on the TCEQ website:

https://www.tceq.texas.gov/permitting/air/nav/air_pbr.html

Available Unit Attribute Forms

OP-UA1 - Miscellaneous and Generic Unit Attributes
OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
OP-UA3 - Storage Tank/Vessel Attributes
OP-UA4 - Loading/Unloading Operations Attributes
OP-UA5 - Process Heater/Furnace Attributes
OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
OP-UA7 - Flare Attributes
OP-UA8 - Coal Preparation Plant Attributes
OP-UA9 - Nonmetallic Mineral Process Plant Attributes
OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
OP-UA11 - Stationary Turbine Attributes
OP-UA12 - Fugitive Emission Unit Attributes
OP-UA13 - Industrial Process Cooling Tower Attributes
OP-UA14 - Water Separator Attributes
OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
OP-UA16 - Solvent Degreasing Machine Attributes
OP-UA17 - Distillation Unit Attributes
OP-UA18 - Surface Coating Operations Attributes
OP-UA19 - Wastewater Unit Attributes
OP-UA20 - Asphalt Operations Attributes
OP-UA21 - Grain Elevator Attributes
OP-UA22 - Printing Attributes
OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
OP-UA25 - Synthetic Fiber Production Attributes
OP-UA26 - Electroplating and Anodizing Unit Attributes

OP-UA27 - Nitric Acid Manufacturing Attributes
OP-UA28 - Polymer Manufacturing Attributes
OP-UA29 - Glass Manufacturing Unit Attributes
OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes
OP-UA31 - Lead Smelting Attributes
OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes
OP-UA33 - Metallic Mineral Processing Plant Attributes
OP-UA34 - Pharmaceutical Manufacturing
OP-UA35 - Incinerator Attributes
OP-UA36 - Steel Plant Unit Attributes
OP-UA37 - Basic Oxygen Process Furnace Unit Attributes
OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes
OP-UA39 - Sterilization Source Attributes
OP-UA40 - Ferroalloy Production Facility Attributes
OP-UA41 - Dry Cleaning Facility Attributes
OP-UA42 - Phosphate Fertilizer Manufacturing Attributes
OP-UA43 - Sulfuric Acid Production Attributes
OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
OP-UA45 - Surface Impoundment Attributes
OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes
OP-UA47 - Ship Building and Ship Repair Unit Attributes
OP-UA48 - Air Oxidation Unit Process Attributes
OP-UA49 - Vacuum-Producing System Attributes
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes
OP-UA51 - Dryer/Kiln/Oven Attributes
OP-UA52 - Closed Vent Systems and Control Devices
OP-UA53 - Beryllium Processing Attributes
OP-UA54 - Mercury Chlor-Alkali Cell Attributes
OP-UA55 - Transfer System Attributes
OP-UA56 - Vinyl Chloride Process Attributes
OP-UA57 - Cleaning/Depainting Operation Attributes
OP-UA58 - Treatment Process Attributes
OP-UA59 - Coke By-Product Recovery Plant Attributes
OP-UA60 - Chemical Manufacturing Process Unit Attributes
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes
OP-UA62 - Glycol Dehydration Unit Attributes
OP-UA63 - Vegetable Oil Production Attributes